

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00047	Connector, dc jack, 4.0x1.7xL16.7 mm, brass nickel plated, molding style	1	
2	30-00404	Wire, 2C TS, 24 AWG, UL2468, 300V, 80C, 3.0 mm, VW-1, PVC, 87A	1	
3	24-00004	Overmold, PVC	1	black



Notes: Functionally equivalent components may be substituted

Wiring I	Wiring Diagram						
50-00047	wire color						
center	black with stripe						
sleeve	black						

Revision:	Date:	Description:	Prepared:	Notes:					
А	02/07/2018	Initial release	GL Digitally signed by GL Date: 2018.02.07 15:39:27 -08'00'	ROHS and REACH compliant	TENSILITY			ITY	
			Verified: AW Digitally signed by AW Date: 2018.02.14 08:16:53 -08'00'	Description: Cable, 1830 mm, 4.0x1.7 mm 50-00047 dc jack to 10		tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com			
			Dimensions are in millimeters.						
			Tolerances: X: ± 0.5 mm						
			X.X: ± 0.3 mm X.XX: ± 0.05 mm	mm tinned, 24 AWG, UL2468, 30-00404 wire	Scale:	1:1		Sheet 1 of 1	

 $\frac{1}{2}$