

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







## **CM-BF548**

## **Blackfin® Core Module**

The Core- Module CM-BF548 is characterized by its numerous peripheral interfaces, its performance in combination with its high speed memory interface and its wide spread application area. The module integrates processor, RAM, flash and power supply at a size of 31x40mm! It is based at the high performance ADSP-BF548 from Analog Devices.

The Core- Module is designed for industrial usage (industrial temperature range). It addresses 64MByte DDR SDRAM via its 16bit wide DDR-RAM bus and has an onboard NOR-flash of 8MByte. The module offers two CAN-, two TWI-, three EPPI-and SPI-interfaces as well as a USB 2.0 OTG and a keypad interface.

#### **Features**

СРИ		Analog Devices BF548 @ 533MHz
RAM		32MByte SDRAM up to 133MHz
FLASH		8MByte
	CAN	2
	PPI	3 (EPPI)
S	SD/SDIO	1
INTERFACES	SPI	3
NTER	SPORT	3
=	TWI/I <sup>2</sup> C	2
	UART	4
	USB 2.0	1 (OTG)
ADDITIONAL FEATURES		Single 3.3V supply voltage On-board core voltage regulator Low voltage reset circuit NAND Flash Interface Keypad Interface
TEMP. RANGE		-40°C to +85°C
VERSIONS		Connector
DIMENSIONS		31x41mm



### **Development Support**

- » DEV-BF548-Lite Development Board
- » DEV-BF548DA-Lite Development Board
- » BLACKSheep® OS
- » uClinux Port available

### **Ordering Information**

	Order No.	Info
	100-1241-1	CM-BF548-C-I-Q25S64F8 (CM-BF548)
	100-1241-1-TR	CM-BF548-C-I-Q25S64F8 (CM-BF548) Tape Reel 50pcs

### **Applications**

- » Multimedia
- » Home Audio/Video
- » Advance vehicle infotainment
- » Mobile communications
- » Security and access control systems
- » Industrial and Instrumentation

BLUETECHNIX Mechatronische Systeme GmbH

Lainzerstraße 162/3 1130 Wien, Austria www.bluetechnix.com Tel.: +43 (1) 9142091 x 0 Fax.: +43 (1) 9142091 x 99 Email: office@bluetechnix.at

