



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Cable tie - PKB 290X4,8 BK - 1005554

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




Cable tie, resistant to UV rays, dimensions: L x W, 290 x 4.8 mm, color: black

Product Features

- ✓ With the UNIFOX-CT ... cable binder tool, the cable binders can be easily tightened and cut off in one step
- ✓ The plastic cable binders are ideal for use with WMTB, KMK 2, and KMK 4 cable markers from Phoenix Contact
- ✓ UV stabilized (black), for use in outdoor systems
- ✓ Transparent, for standard applications
- ✓ The cable binders can be used indoors and outdoors even under unfavorable industrial conditions
- ✓ For bundling control lines and cables

Key commercial data

Packing unit	1 PCE
Minimum order quantity	1000 PCE
Catalog page	Page 382 (CL2-2011)
GTIN	 4 017918 012625
Custom tariff number	39269097
Country of origin	UNITED STATES

Technical data

General

Length (b)	290 mm
Width (a)	4.8 mm
Color	black
Inflammability class according to UL 94	V2
Ambient temperature (operation)	-40 °C ... 85 °C
Material	PA

Cable tie - PKB 290X4,8 BK - 1005554

Classifications

ETIM

ETIM 2.0	EC000046
ETIM 3.0	EC000046
ETIM 4.0	EC000046
ETIM 5.0	EC000046

UNSPSC

UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703
UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703

eCl@ss

eCl@ss 4.0	27140702
eCl@ss 4.1	27140702
eCl@ss 5.0	27140702
eCl@ss 5.1	27140702
eCl@ss 6.0	27140702
eCl@ss 7.0	27140702