



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Conductor marker carrier - PATO 4/15 - 1013148

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Conductor marker carrier, transparent, unlabeled, mounting type: clip on, cable diameter range: 6.7 - 10 mm, lettering field size: 4 x 15 mm

Why buy this product

- Can be labeled using UC-WMT ... and US-WMT ... plastic labels or EMT insert strips
- These marking collars are used for subsequent labeling of systems that have already been wired

Key Commercial Data

| | |
|------------------------|---------------|
| Packing unit | 500 STK |
| Minimum order quantity | 500 STK |
| GTIN | |
| GTIN | 4017918013561 |

Technical data

Dimensions

| | |
|----------------|------------------|
| Length (b) | 15 mm |
| Width (a) | 12 mm |
| Cable diameter | 6.7 mm ... 10 mm |

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -50 °C ... 80 °C |
|---------------------------------|------------------|

General

| | |
|--|---------------|
| Color | transparent |
| Type | Profile |
| Components | Silicone-free |
| Flammability rating according to UL 94 | V0 |
| Material | PVC |
| Marking mounting type | clip on |

Conductor marker carrier - PATO 4/15 - 1013148

Technical data

Standards and Regulations

| | |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>