



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Splice box - FOC-FDX20-PP-LCQ6-MM - 1019705

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



DIN rail splice box, without pigtails, for 12x LC duplex

DIN rail splice box, 12x LC duplex couplings

Product Description

DIN rail splice box of the FDX 20 series, equipped with 12x LC duplex couplings, splice holder (for separately sold shrink and crimp splice protection) on a patented splice comb made from powder-coated sheet steel. Cable insertion possible via cable gland either at top or bottom. Housing (2-part) prepared for DIN rail mounting through rear-side adapter (this can also be mounted on the side).

Scope of supply:

DIN rail housing with integrated splice comb (mounted), equipped with 12x LC duplex couplings, 1x splice holder, 1x cable gland (M20x1.5)

Why buy this product

- ✓ Intuitive front panel operation and clear control cabinet layout thanks to uniform design
- ✓ Flexible DIN rail mounting possible in three positioning directions
- ✓ Perfectly sized and patented pigtail tray, for convenient splicing and compact bending radii.
- ✓ 12 duplex front connections and compact dimensions, for more space in the control cabinet
- ✓ Suitable for industrial applications
- ✓ Continuously reliable data connection, thanks to extensively tested components
- ✓ 3-stage strain relief
- ✓ easy to install
- ✓ including cable gland
- ✓



Key Commercial Data

Packing unit	1 STK
GTIN	
GTIN	4055626701080

Technical data

Mechanical characteristics

Splice box - FOC-FDX20-PP-LCQ6-MM - 1019705

Technical data

Mechanical characteristics

Number of slots	12
Connection profile	LC connectors
Fiber type	GOF
Ferrule diameter	1.25 mm
Insertion/withdrawal cycles	≥ 500
Connection method	Cable gland M20
External cable diameter	6 mm ... 12 mm
Cable outlet	above and below
Type of cable	For all common cable types
Color	traffic grey A RAL 7042
Mounting type	DIN rail mounting
Degree of protection	IP20
Type	Rail-mountable module
No. of cable outlets	2
Type of the screw connection	M20 x 1.5
Type of note	Order information:
Note	In addition, shrink splice protection (Order No.: 1019676) or crimp splice protection (Order No.: 1019678) must be ordered separately.

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (assembly)	0 °C ... 50 °C
Degree of protection	IP20 (according to IEC 60529)

Material data

Flammability rating according to UL 94	V0
Housing material	Sheet steel
Housing surface material	Powder-coated, gray
Ferrule material	Zirconia ceramics
Housing width	40 mm
Depth	115 mm
Height	130 mm

Line characteristics

Type of cable	For all common cable types
Cable type	Fiberglass
Transmission medium	FO
Number of fibers	24
Fiber	GOF


Standards and Regulations

Resistance to UV radiation	yes
Flammability rating according to UL 94	V0

Splice box - FOC-FDX20-PP-LCQ6-MM - 1019705

Drawings

Dimensional drawing



DIN rail distributor 6x LC quad

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>