



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Non-invasive AC Current Sensor (15A max)

SKU: 101990060

(images/product/101990060 1_02.jpg)

Description

What is CT sensors

Current transformers (CTs) are sensors that are used for measuring alternating current. They are particularly useful for measuring whole building electricity consumption (or generation for that matter).

The split core type such as the CT in the picture above, is particularly suitable for DIY use it can be clipped straight on to either the live or neutral wire coming into the building without having to do any high voltage electrical work.

Features

Applications

- Suitable for the current measuring
- Monitoring and protection of AC motor
- Lighting equipment
- Air compressor

Specification

- Input Current: 0~15A AC
- Output Mode: 0~1V
- Non-linearity: $\pm 3\%$
- Build-in sampling resistance (RL): 124Ω
- Resistance Grade: Grade B
- Work Temperature: $-25^{\circ}\text{C} \sim +70^{\circ}\text{C}$
- Dielectric Strength(between shell and output): 1000V AC/1min 5mA
- Leading Wire in Length: 1m
- Open Size: 13mm x 13mm
- Fire resistance property: in accordance with UL94-VO