



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




General ordering data

Order No.	1028400000
Part designation	WFF 70
Version	Stud terminal, 70 mm ² , Threaded stud connection, Wemid, dark beige, TS 35
EAN	4008190083311
Qty.	10 pc(s).

Product notes

Note, ordering data	The rated voltage is reduced to 800 V when using a cable lug to DIN 46234 with 70 and 95 mm ² .
Note, accessories	WAH 70 in blue, order no. 1064580000

PT OKIECEX/ATEX rating data

EU-type examination certificate	KEMA98ATEX1684U
Download, German	KEMA98ATEX1684U_d.pdf
Download English	KEMA98ATEX1684U_e.pdf
ATEX voltage	1100 V
ATEX current	167 A
ATEX conductor cross-section	70 mm ²
Voltage when using cross-connections	CrossConnectionGuide.pdf
Operating temperature range	Einsatztemperaturbereich siehe EG-Baumusterprüfbescheinigung/IECEx-Certificate of Conformity
Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

Additional technical data

Colour of insulating material	dark beige
Connection direction	on side
End plate required	No
Explosion-tested version "Ex e"	Yes
Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	No

Additional technical data

No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	closed
Operating temperature range	- 50 °C, + 120 °C
Product family	W-Series
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0
Version	Feed-through terminal

CSA rating data

Voltage (CSA)	600 V
CSA current	170 A
Min. cross-section (CSA)	AWG 14
Max. cross-section (CSA)	AWG 2/0

Conductors for clamping (rated connection)

Type of connection	Threaded stud connection
Connection direction	on side
Flexible, min.	2.5 mm ²
Flexible, max.	95 mm ²

Dimensions

Width	32 mm
Height of lowest version	64 mm
Length	132 mm
Weight	176.5 g
TS 35 offset	66 mm

Rating data

Rated cross-section	70 mm ²
Rated voltage	1,000 V
Rated impulse voltage	8 kV
Rated current	192 A
Current with max. conductor	232 A
Pollution severity	3

Strap connection

Gauge to EN 50043	C6
Strap 1, max.	4 x 20 x 1
Strap 1, min.	2 x 15.5 x 0.8
Strap 2, max.	6 x 15.5 x 0.8
Strap 2, min.	4 x 15.5 x 0.8

Stud connection

2 cable lugs to DIN 46234	16...70 mm ²
2 cable lugs to DIN 46234	2.5...70 mm ²
Cable lug to DIN 46234	16...70 mm ²
Cable lug to DIN 46234	2.5...95 mm ²
Clamping range, max.	95 mm ²

Stud connection

Clamping range, min.	2.5 mm ²
Stud size for spade connection	M 8
Tightening torque range	6.0...12 Nm

UL rating data

Voltage (UL)	1,000 V
Current (UL)	175 A
Min. cross-section (UL)	AWG 14
Max. cross-section (UL)	AWG 2/0

Approvals

Approvals institutes

**Downloads**

STEP	1028400000_16357_WFF_70_STP.stp
------	---------------------------------

Classifications

eClass 4.1	NK
eClass 5.0	NK
eClass 5.1	NK

Similar products

Order No.	Part designation	Version
1028300000	WFF 35	Stud terminal, 35 mm ² , Threaded stud connection, Wemid, dark beige, TS 35
1028380000	WFF 35 BL	Stud terminal, 35 mm ² , Threaded stud connection, Wemid, blue, TS 35
1028480000	WFF 70 BL	Stud terminal, 70 mm ² , Threaded stud connection, Wemid, blue/light blue, TS 35
1028500000	WFF 120	Stud terminal, 120 mm ² , Threaded stud connection, Wemid, dark beige, TS 35
1028580000	WFF 120 BL	Stud terminal, 120 mm ² , Threaded stud connection, Wemid, blue, TS 35

1857540000	WFF 120/M12/AH	Stud terminal, 120 mm ² , Screw connection, Wemid, dark beige, TS 35
1028600000	WFF 185	Stud terminal, 185 mm ² , Threaded stud connection, Wemid, dark beige, TS 35
1028680000	WFF 185 BL	Stud terminal, 185 mm ² , Threaded stud connection, Wemid, blue, TS 35
1028700000	WFF 300	Stud terminal, 300 mm ² , Threaded stud connection, Wemid, dark beige, TS 35