

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China
















<TABLE 1>

	MATERIAL NO.	ORDER NO.	MATERIAL	PACKING	COLOR
TYPE - C	1040040911	104004-0911	LCP	TRAY	BLACK





NOTE


1. MATES WITH:


(MOLEX SERIES NO. - 111014, 111015, 111005, 111041, 111019, 111020)

- 2. SHROUD GEOMETRY AND ASSEMBLY WITH USB MINI-B CONNECTOR ARE ACCORDING TO USCAR STD 999-U-USB-Z01
- 3. FINISHES
 - TERMINAL :

CONTACT AREA: Au 0.754m MIN. SOLDER TAIL AREA : TIN 3.84m MIN.

- UNDER PLATING : NI 1.04m MIN.
- SHIELD CASE :
 - 3.04m MIN. TIN OVER NI 1.04m MIN.
- FITTING NAIL:
 - 3.04m MIN. TIN OVER NI 1.04m MIN.
- 4. UNLESS OTHERWISE SPECIFIED, TYPICAL RECOMMENDED PCB MANUFACTURING TOLERANCE IS ±0.05
- 5. PACKAGING IS TRAY:
 - (48 PCS/TRAY, 5 TRAY/TRAY BOX, 240 PCS/TRAY BOX, 960 PCS/CARTON BOX)
- 6. PRODUCT SPECIFICATION: PS-49616-001
- 7. PACKAGING INFORMATION: PK-104004-003
- 8. PCB THICKNESS: 2.36mm(REFERENCE)





<PARTS LIST>

- 1	NO.	PART NAME	MATERIAL				
[1	SHROUD-C	LCP, GLASS FILLED, UL94 V-0				
[2	RECEPTACLE HOUSING	LCP, GLASS FILLED, UL94 V-0				
[Э	CONTACT HOUSING	LCP, GLASS FILLED, UL94 V-0				
[4	CONTACT TERMINAL	COPPER ALLOY				
[5	SHIELD CASE	PHOSPHOR BRONZE				
[6	BOARD LOCKS PIN	BRASS				

2015/04/27	2015/05/04 N	QUALITY SYMBOLS	GENERAL TO (UNLESS SPE		DIMENSION S MM ONI	_Y	SCALE 5:1	METRIC		THIRD ANGLE PROJECTION
ŏ	I 2015 SCRIPTION	V =0	### PLACES # 3 PLACES #	± ±	CHECKED BY	009/06/17 DATE			RTICAL -	CONN.
KTR2015-	IYCHO I	V =0	2 PLACES ± 0.19 1 PLACE ± 0.2 ANGULA	5 ± AR ± 1 °	APPROVED BY JYCHOI	009/06/17 DATE 2014/08/01	MOLEX INCOR			
CHKD NO.	APPR:			APPLICABLE FMAIN	SIZE THIS DRAW	BLE1 VING CONTA	AINS INFOR	SD-10400	T IS PROPRIE	SHEET NO. 1 OF 1 TARY TO MOLEX
- 731	1 02	_	1 -		I -	ILU AND S	JI ROOLD INC	- 0360		TEN TENNISSION