



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



PiShow 2.4 inch Resistive Touch Display

SKU 104990222



DESCRIPTION

I've already started watching movies on my Raspberry Pi, and you are still dealing with cables and a missing mouse. Yes, this is the Pishow 2.4" Resistive Touch Display, no need for cable or extra power source, no need for mouse, just attach it directly onto your Raspberry Pi A/B, Model A+/B+, or Rpi 2, then you are ready to roll. The driver is very easy to setup as well, we've packaged the system kernel for you, all you need to do is simply upload it to the operation system on your Pi. The kernel package supports most of OS on Pi such as Rasbian Debian, Fedora and Ubuntu.

The display communicates with your Raspberry Pi through a high speed SPI interface (SCK, MOSI, MISO, CE0, CE1), which can reach up to 64MHz clock speed with over-clock. You can use it as X window port to display images or videos. Some of the GPIOs are also used for control purposes, for example it uses GPIO #23 to RESET the screen, GPIO #24 for power supply, GPIO #18 for backlight control and GPIO #22 for touch interrupts. The rest of GPIOs are not used.

The size of the display is 2.4" in diagonal, a bit smaller than the previous 2.8" version, but it still keeps the 320x240 QVGA resolution and also offers 16-bit color pixels beneath the resistive touch screen.

It would be an absolutely pleasure adding this to your Raspberry Pi project. Don't ask me why, if you try it you'll know it.

FEATURES

- 320 x 240 Resolution
- Resistive touch screen
- AIO (All in One) Driver Pack
- Support up to 64MHz with over-clock.
- Adjustable LED Backlight Hardware through PWM
- HAT compatible
- High speed SPI interface

TECHNICAL SPECIFICATIONS

- Resolution: 320x240
- Display Colors: 262K (6-bit)
- Signal Interface: SPI
- Voltage: 5V via Pin Header
- Current: more than 65mA (Test conditions: include RPI B Plus.)
- Power Consumption: more than 0.325W (Test conditions: include RPI B Plus.)
- Backlight Brightness: 330 cd/m2 (Typ.)
- Dimensions: 66.294mm x 57.15mm x 14mm
- Weight: 32g

WHAT'S INCLUDED

- 1x Battery Indicator
- 1x 1050mAh 3.7V Lipo Battery