

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







BATTERY CONTACTS






"A" • "AA" • "AAA" • "N" SIZE PC BUTTON & SPRING CONTACTS



- · Ideal contacts for "A" · "AA" · "AAA" · "N" size batteries
- Space saving design installs directly onto the PC board
- Contacts available for .062 and .093 thick PC boards
- Reliable spring and/or button assures low contact resistance













MATERIAL: Frame: .015 Steel, Tin Plate Uses Cat. No. 211 Spring Contact

MATERIAL: Frame: .015 Steel, Tin Plate










SURFACE MOUNT BATTERY CONTACTS



CAT. NO. 5230


CAT. NO. 5230TR

- · Economical & reliable contacts are ideal for surface mount applications · Unique spring tension contacts adjust to variations in battery length
- Reliable spring tension contacts assure low contact resistance
- SMT solder tail with "flow-hole" design for increased joint strength MATERIAL: 010 Spring Steel, Nickel Plate



13 inch reel (400 pieces per reel)







Tape and Reel Spec's:32mm wide; 12mm pitch; 13 inch reel (400 pieces per reel)


• ECONOMICAL • SPACE SAVING


PC BATTERY CONTACTS

· Ideal for self-contained battery compartments Contact us for modifications and custom design



















CAT. NO. 2990 CAT. NO. 108-2 CAT. NO. 109-2 .012 Thick, Spring Steel, Nickel Plate .008 Thick, Phospher Bronze, Nickel Plate









.008 Thick, Spring Steel Nickel Plate