



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## ZB 5 :UNBEDRUCKT

Order No.: 1050004

The illustration shows the variants of the ZB 5



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1050004>

Zack strip, unprinted, 10-section, for individual labeling with M-PEN, ZB-T or CMS system, pack is sufficient for 100 terminal blocks, for a terminal width of 5.2 mm, color: White

### Commercial data

|                          |                    |
|--------------------------|--------------------|
| EAN                      | 4017918015473      |
| Pack                     | 10 pcs.            |
| Customs tariff           | 39269097           |
| Weight/Piece             | 0.001266 KG        |
| Catalog page information | Page 487 (CL-2009) |

### Product notes

WEEE/RoHS-compliant since:  
01/01/2005



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### General

|                                    |                             |
|------------------------------------|-----------------------------|
| Width (a)                          | 5 mm                        |
| Color                              | white                       |
| Inflammability class acc. to UL 94 | V2                          |
| Wipe resistance                    | DIN EN 61010-1 (VDE 0411-1) |
|                                    | DIN VDE 0611                |

|                                 |                                |
|---------------------------------|--------------------------------|
| Ambient temperature (operation) | -40 °C ... 100 °C              |
| Components                      | free from silicone and halogen |
| Pitch                           | 5.2 mm                         |
| Material                        | PA                             |
| Pitch                           | 5.2 mm                         |

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;