## mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Order No.       1050050000         Part designation       WAP 2.5-10 GR         Version       Modular terminal, accessories, End and intermediate plate, grey, 1.5 mm         EAN       4008190455484         Qty.       50 pc(s).         Additional technical data       Installation advice         Installation advice       Direct mounting         UL 94 flammability rating of insulation material       V0         Dimensions       Vidth         Kidthonal       1.5 mm         Length       56 mm         TS 35 offset       66 mm         End plate       Colour         Gour       grey         Function       End plate         Height       33.5 mm         Length       56 mm         Material       Wemid         Snap-on       No         UL 94 flammability rating of insulation material       V0		
Part designation       WAP 2.5-10 GR         Version       Modular terminal, accessories, End and intermediate plate, grey, 1.5 mm         EAN       4008190455484         Qty.       50 pc(s).         Additional technical data       Installation advice         Installation advice       Direct mounting         UL 94 flammability rating of insulation material       V0         Dimensions       Vidth         Width       1.5 mm         Length       56 mm         TS 35 offset       66 mm         End plate       Colour         Colour       grey         Function       End plate         Height       33.5 mm         Length       56 mm         Material       Wemid         Snap-on       No         UL 94 flammability rating of insulation material       V0	General ordering data	
Version       Modular terminal, accessories, End and intermediate plate, grey, 1.5 mm         EAN       4008190455484         Qty.       50 pc(s).         Additional technical data       Installation advice         Installation advice       Direct mounting         UL 94 flammability rating of insulation material       V0         Dimensions       V0         Width       1.5 mm         Length       56 mm         TS 35 offset       66 mm         End plate       Colour         Grey       Function         Function       End plate         Height       33.5 mm         Length       56 mm         Material       Wemid         Snap-on       No         UL 94 flammability rating of insulation material       V0		
EAN       4008190455484         Qty.       50 pc(s).         Additional technical data       Installation advice         UL 94 flammability rating of insulation material       V0         Dimensions       V0         Width       1.5 mm         Length       56 mm         TS 35 offset       66 mm         End plate       End plate         Height       33.5 mm         Length       56 mm         TS 35 offset       66 mm         End plate       Uleget         Height       33.5 mm         Length       56 mm         Vernid       Sa.5 mm         Length       50 mm         Function       End plate         Height       1.3 mm         Length       56 mm         UL 94 flammability rating of insulation material       V0         Approvals       Vernid		
Qty.     50 pc(s).       Additional technical data       Installation advice     Direct mounting       UL 94 flammability rating of insulation material     V0       Dimensions     V0       Width     1.5 mm       Length     56 mm       TS 35 offset     66 mm       End plate       Colour     grey       Function     End plate       Height     33.5 mm       Length     56 mm       Material     Wemid       Snap-on     No       UL 94 flammability rating of insulation material     V0	Version	
Additional technical data         Installation advice       Direct mounting         UL 94 flammability rating of insulation material       V0         Dimensions         Width       1.5 mm         Length       56 mm         TS 35 offset       66 mm         End plate         Colour       grey         Function       End plate         Height       33.5 mm         Length       56 mm         Material       Wemid         Snap-on       No         UL 94 flammability rating of insulation material       V0	EAN	4008190455484
Installation advice       Direct mounting         UL 94 flammability rating of insulation material       V0         Dimensions         Width       1.5 mm         Length       56 mm         TS 35 offset       66 mm         End plate         Colour       grey         Function       End plate         Height       33.5 mm         Length       56 mm         Material       Wemid         Snap-on       No         UL 94 flammability rating of insulation material       V0	Qty.	50 pc(s).
Installation advice       Direct mounting         UL 94 flammability rating of insulation material       V0         Dimensions         Width       1.5 mm         Length       56 mm         TS 35 offset       66 mm         End plate         Colour       grey         Function       End plate         Height       33.5 mm         Length       56 mm         Material       Wemid         Snap-on       No         UL 94 flammability rating of insulation material       V0		
UL 94 flammability rating of insulation material       V0         Dimensions       1.5 mm         Width       1.5 mm         Length       56 mm         TS 35 offset       66 mm         End plate       60 mm         Colour       grey         Function       End plate         Height       33.5 mm         Length       56 mm         Material       Wemid         Snap-on       No         UL 94 flammability rating of insulation material       V0		
Dimensions         Width       1.5 mm         Length       56 mm         TS 35 offset       66 mm         End plate         Colour       grey         Function       End plate         Height       33.5 mm         Length       56 mm         Material       Wemid         Snap-on       No         UL 94 flammability rating of insulation material       V0		
Width1.5 mmLength56 mmTS 35 offset66 mmEnd plateColourgreyFunctionEnd plateHeight33.5 mmLength56 mmMaterialWemidSnap-onNoUL 94 flammability rating of insulation materialV0	UL 94 flammability rating of insulation material	V0
Width1.5 mmLength56 mmTS 35 offset66 mmEnd plateColourgreyFunctionEnd plateHeight33.5 mmLength56 mmMaterialWemidSnap-onNoUL 94 flammability rating of insulation materialV0		
Length56 mmTS 35 offset66 mmEnd plateColourgreyFunctionEnd plateHeight33.5 mmLength56 mmMaterialWemidSnap-onNoUL 94 flammability rating of insulation materialV0		
TS 35 offset66 mmEnd plategreyColourgreyFunctionEnd plateHeight33.5 mmLength56 mmMaterialWemidSnap-onNoUL 94 flammability rating of insulation materialV0		
End plateColourgreyFunctionEnd plateHeight33.5 mmLength56 mmMaterialWemidSnap-onNoUL 94 flammability rating of insulation materialV0		
ColourgreyFunctionEnd plateHeight33.5 mmLength56 mmMaterialWemidSnap-onNoUL 94 flammability rating of insulation materialV0	TS 35 offset	66 mm
ColourgreyFunctionEnd plateHeight33.5 mmLength56 mmMaterialWemidSnap-onNoUL 94 flammability rating of insulation materialV0		
FunctionEnd plateHeight33.5 mmLength56 mmMaterialWemidSnap-onNoUL 94 flammability rating of insulation materialVO		
Height33.5 mmLength56 mmMaterialWemidSnap-onNoUL 94 flammability rating of insulation materialV0		
Length       56 mm         Material       Wemid         Snap-on       No         UL 94 flammability rating of insulation material       V0		
Material     Wemid       Snap-on     No       UL 94 flammability rating of insulation material     V0		
Snap-on     No       UL 94 flammability rating of insulation material     V0       Approvals		
UL 94 flammability rating of insulation material V0 Approvals		
Approvals		
	UL 94 flammability rating of insulation material	V0
Pprovais institutes	Approvals institutes	PG
ME25		ME25

eClass 4.1	27-14-11-99	
eClass 5.0	27-14-11-33	
eClass 5.1	27-14-11-33	

## Similar products

Order No.		Version
1050000000	WAP 2.5-10	Modular terminal, accessories, End and intermediate plate, dark beige, 1.5 mm
1050080000	WAP 2.5-10 BL	Modular terminal, accessories, End and intermediate plate, blue/light blue, 1.5 mm
1050070000	WAP 2.5-10 BR	Modular terminal, accessories, End and intermediate plate, brown, 1.5 mm
1050020000	WAP 2.5-10 GE	Modular terminal, accessories, End and intermediate plate, yellow, 1.5 mm



Product catalogue | Terminals | Screwing technology | W-series modular terminals | Accessories | End and partition plates | WAP 2.5-10

1072200000	WAP 2.5-10 GN	Modular terminal, accessories, End and intermediate plate, green, 1.5 mm
1050060000	WAP 2.5-10 OR	Modular terminal, accessories, End and intermediate plate, Orange, 1.5 mm
1050040000	WAP 2.5-10 RT	Modular terminal, accessories, End and intermediate plate, red, 1.5 mm
1050010000	WAP 2.5-10 SW	Modular terminal, accessories, End and intermediate plate, black, 1.5 mm
1072210000	WAP 2.5-10 VI	Modular terminal, accessories, End and intermediate plate, violet, 1.5 mm
1050090000	WAP 2.5-10 WS	Modular terminal, accessories, End and intermediate plate, white, 1.5 mm

