



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## ZB 6,LGS:FORTL.ZAHLEN 1-10

Order No.: 1051016:0001

The illustration shows the version ZB 6:UNBEDRUCKT

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1051016:0001>

Zack marker strip, 10-section, horizontally labeled with the consecutive numbers: 1 ... 10, white, Width: 6 mm

### Commercial data

EAN	4017918195557
Pack	10 pcs.
Customs tariff	39269097
Weight/Piece	0.00158 KG

### Product notes

WEEE/RoHS-compliant since:  
01/01/2003<http://>

[www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### General data

Color	white
Pitch	6.00 mm
Material	PA
Temperature range	-40 °C ... 100 °C
Inflammability class acc. to UL 94	V2

Components	free from silicone and halogen
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;