



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Zack marker strip - ZB 6,LGS:1-9 - 1051126


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Zack marker strip, Strip, white, Labeled, Printed horizontally: Consecutive numbers 1 - 9, Mounting type: Snap into tall marker groove, For terminal block width: 6.2 mm, Lettering field: 10.5 x 6.15 mm

The illustration shows the version ZB 6:UNBEDRUCKT

Key commercial data

Packing unit	1
Minimum order quantity	10
Catalog page	Page 60 (IF-2002)
GTIN	 4 017918 015930
Custom tariff number	39269097
Country of origin	GERMANY

Technical data

General

Note	10 identically marked strips make up one packing unit (PU).
Width (a)	6 mm
Color	white
Inflammability class according to UL 94	V2
Wipe resistance	DIN 30646
Wipe resistance	DIN VDE 0611
Ambient temperature (operation)	-40 °C ... 100 °C
Components	free from silicone and halogen
Material	PA
Printing direction	Printed horizontally
Printing	Consecutive numbers 1 - 9
Number of individual labels	9

Classifications

eclass

eCl@ss 4.0	24190208
eCl@ss 4.1	24190208

Zack marker strip - ZB 6,LGS:1-9 - 1051126

Classifications

eclass

eCl@ss 5.0	27149103
eCl@ss 5.1	27149103
eCl@ss 6.0	27141137

etim

ETIM 2.0	EC000761
ETIM 3.0	EC000761
ETIM 4.0	EC000761

unspsc

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410