



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





#### General ordering data

Order No.	1051260000
Part designation	WTA 5/1
Version	Modular terminal, accessories, Test adapter
EAN	4008190161897
Qty.	25 pc(s).

#### Product notes

Note, technical data	Rated current 6 A
----------------------	-------------------

#### Additional technical data

Installation advice	Direct mounting
---------------------	-----------------

#### CSA rating data

Voltage (CSA)	300 V
CSA current	6 A

#### Conductors for clamping (additional connection)

Clamping range, max.	1 mm <sup>2</sup>
Rated cross-section	0.75 mm <sup>2</sup>

#### Conductors for clamping (rated connection)

Type of connection	Plug-in connection
No. of connections	1
Stripping length	6 mm
Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	1 mm <sup>2</sup>
Flexible, min.	1 mm <sup>2</sup>
Flexible, max.	1 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	1 mm <sup>2</sup>

#### Dimensions

Width	5 mm
-------	------

#### Dimensions

Height of lowest version	68.2 mm
Length	17 mm

#### Rating data

Rated cross-section	0.75 mm <sup>2</sup>
Rated voltage	250 V
Rated current	6 A

#### Test adapter

Function	Test adapter
With snap-in pegs	No

#### Test adapter dimensions

Height with TS 35	68.2 mm
With snap-in pegs	No

#### Test adapter rated data

Rated voltage	250 V
---------------	-------

#### UL rating data

Voltage (UL)	300 V
Current (UL)	6 A

#### Approvals

Approvals institutes



#### Classifications

eClass 4.1	27-14-11-99
eClass 5.0	27-14-11-45
eClass 5.1	27-14-11-45

#### Similar products

Order No.	Part designation	Version
1062060000	WTA 5/10	Modular terminal, accessories, Test adapter