



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



		REVISIONS																																																																											
		REV	DESCRIPTION	DATE	APPROVED																																																																								
		042	UPDATED	8/1/94	BB																																																																								
<p>.XXX = in XX.X = mm</p>																																																																													
<table><tr><th>ELECTRICAL</th><th>MECHANICAL</th><th>ENVIRONMENTAL</th></tr><tr><td>Nominal Impedance (Ohms) 50</td><td>Interface Dimensions MIL-STD-348A, Fig. 304.2</td><td>Temperature Rating -65°C to +125°C</td></tr><tr><td>Frequency Range (GHz) DC to 11</td><td>Recommended Mating</td><td>Vibration MIL-STD-202, Method 204, Condition B</td></tr><tr><td>Volt Rating (VRMS MAX) @ Sea Level 1000</td><td>Torque N/A</td><td>Shock MIL-STD-202, Method 213, Condition I</td></tr><tr><td>VSWR N/A</td><td>Mating Characteristics:</td><td>Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +115°C</td></tr><tr><td>Insertion Loss (dB MAX) N/A</td><td>Insertion (MAX lbs) 2.0</td><td>Moisture Resistance MIL-STD-202, Method 106</td></tr><tr><td>RF Leakage (dB MIN) N/A</td><td>Withdrawal (MIN oz) 2.0</td><td>Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray</td></tr><tr><td>Corona, 70,000 Ft (VRMS MIN) 500</td><td>Force to Engage and Disengage (in-lbs MAX) 3.0</td><td></td></tr><tr><td>Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 2500</td><td>Center Contact Captivation</td><td></td></tr><tr><td>Contact Resistance (Milliohms MAX)</td><td>Axial (lbs) 6.0</td><td></td></tr><tr><td>Center Contact 1.0</td><td>Radial (in-oz) 4.0</td><td></td></tr><tr><td>Outer Contact .2</td><td></td><td></td></tr><tr><td>RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 1500</td><td></td><td></td></tr><tr><td>I.R.(Megohms MIN) 5000</td><td></td><td></td></tr></table>		ELECTRICAL	MECHANICAL	ENVIRONMENTAL	Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 304.2	Temperature Rating -65°C to +125°C	Frequency Range (GHz) DC to 11	Recommended Mating	Vibration MIL-STD-202, Method 204, Condition B	Volt Rating (VRMS MAX) @ Sea Level 1000	Torque N/A	Shock MIL-STD-202, Method 213, Condition I	VSWR N/A	Mating Characteristics:	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +115°C	Insertion Loss (dB MAX) N/A	Insertion (MAX lbs) 2.0	Moisture Resistance MIL-STD-202, Method 106	RF Leakage (dB MIN) N/A	Withdrawal (MIN oz) 2.0	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray	Corona, 70,000 Ft (VRMS MIN) 500	Force to Engage and Disengage (in-lbs MAX) 3.0		Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 2500	Center Contact Captivation		Contact Resistance (Milliohms MAX)	Axial (lbs) 6.0		Center Contact 1.0	Radial (in-oz) 4.0		Outer Contact .2			RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 1500			I.R.(Megohms MIN) 5000			<table><tr><td>HOUSING</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303</td><td>NICKEL PLATE PER QQ-N-290</td></tr><tr><td>DIELECTRIC</td><td>TFE FLUOROCARBON PER ASTM-D-1457</td><td>N/A</td></tr><tr><td>CENTER CONTACT</td><td>BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>COMPONENT</td><td>MATERIAL</td><td>FINISH</td></tr></table>		HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	NICKEL PLATE PER QQ-N-290	DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A	CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204	COMPONENT	MATERIAL	FINISH	<table><tr><td rowspan="3">UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± 1°</td><td>DRAWN BY ESC DATE 11/30/70</td><td rowspan="3">AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599</td></tr><tr><td>CHECKED BY PRS 12/2/70</td></tr><tr><td>APPD BY RPS 12/2/70</td></tr><tr><td>These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.</td><td>USE ASS'Y PROCEDURE NO. AP. N/A</td><td>TITLE OSN FLANGE MOUNT JACK RECEPTACLE SOLDER POT TERMINAL</td></tr><tr><td colspan="2">SIZE B</td><td>CODE IDENT NO. 26805</td><td>3052-0000-10</td><td>REV 042</td></tr><tr><td colspan="2">SCALE 2:1</td><td colspan="3">SHEET 1 OF 1</td></tr></table>		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± 1°	DRAWN BY ESC DATE 11/30/70	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599	CHECKED BY PRS 12/2/70	APPD BY RPS 12/2/70	These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASS'Y PROCEDURE NO. AP. N/A	TITLE OSN FLANGE MOUNT JACK RECEPTACLE SOLDER POT TERMINAL	SIZE B		CODE IDENT NO. 26805	3052-0000-10	REV 042	SCALE 2:1		SHEET 1 OF 1		
ELECTRICAL	MECHANICAL	ENVIRONMENTAL																																																																											
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 304.2	Temperature Rating -65°C to +125°C																																																																											
Frequency Range (GHz) DC to 11	Recommended Mating	Vibration MIL-STD-202, Method 204, Condition B																																																																											
Volt Rating (VRMS MAX) @ Sea Level 1000	Torque N/A	Shock MIL-STD-202, Method 213, Condition I																																																																											
VSWR N/A	Mating Characteristics:	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +115°C																																																																											
Insertion Loss (dB MAX) N/A	Insertion (MAX lbs) 2.0	Moisture Resistance MIL-STD-202, Method 106																																																																											
RF Leakage (dB MIN) N/A	Withdrawal (MIN oz) 2.0	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray																																																																											
Corona, 70,000 Ft (VRMS MIN) 500	Force to Engage and Disengage (in-lbs MAX) 3.0																																																																												
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 2500	Center Contact Captivation																																																																												
Contact Resistance (Milliohms MAX)	Axial (lbs) 6.0																																																																												
Center Contact 1.0	Radial (in-oz) 4.0																																																																												
Outer Contact .2																																																																													
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 1500																																																																													
I.R.(Megohms MIN) 5000																																																																													
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	NICKEL PLATE PER QQ-N-290																																																																											
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A																																																																											
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204																																																																											
COMPONENT	MATERIAL	FINISH																																																																											
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± 1°	DRAWN BY ESC DATE 11/30/70	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599																																																																											
	CHECKED BY PRS 12/2/70																																																																												
	APPD BY RPS 12/2/70																																																																												
These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASS'Y PROCEDURE NO. AP. N/A	TITLE OSN FLANGE MOUNT JACK RECEPTACLE SOLDER POT TERMINAL																																																																											
SIZE B		CODE IDENT NO. 26805	3052-0000-10	REV 042																																																																									
SCALE 2:1		SHEET 1 OF 1																																																																											