



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**Industrial Ethernet
IE-BSS-V14M-SCRJ-MM-C**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



PushPull plug-in connector set according to IEC
61076-3-117 ver.14 (PROFINET), metal incl. SC insert

General ordering data

| | |
|------------|--|
| Type | IE-BSS-V14M-SCRJ-MM-C |
| Order No. | 1058120000 |
| Version | Flange FO, Variant 14 standardized flange, SCRJ Duplex coupling, Multimode, POF |
| GTIN (EAN) | 4032248799237 |
| Qty. | 10 pc(s). |

Data sheet

**Industrial Ethernet
IE-BSS-V14M-SCRJ-MM-C**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Net weight 26.86 g

Temperatures

| | | | |
|-----------------------------|-------|--------------------------|----------------|
| Operating temperature, max. | 70 °C | Operating temperature | -40 °C...70 °C |
| Storage temperature | | Installation temperature | |

General data

| | | | |
|---------------------------|----------------|------------------------|--|
| Colour | Miscellaneous | Connection 1 | SCRJ |
| Connection 2 | | Description of article | Variant 14 standardized flange, SCRJ Duplex coupling |
| | SCRJ | | |
| Fibre type | Multimode, POF | Housing main material | Zinc diecast |
| Insertion loss | ≤ 0.4 dB | Plugging cycles | 500 |
| Return loss (attenuation) | ≥ 30 dB | Seal material | EPDM |
| Type of mounting | 2 screws | | |

Standards

Connector standard IEC 61076-3-117 Var. 14, IEC 61754-24

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC001121 | ETIM 4.0 | EC001121 |
| ETIM 5.0 | EC001121 | ETIM 6.0 | EC001121 |
| eClass 5.1 | 27-26-12-03 | eClass 6.2 | 27-25-05-04 |
| eClass 7.1 | 27-25-05-04 | eClass 8.1 | 19-17-01-25 |
| eClass 9.0 | 19-17-01-25 | | |

Approvals

Approvals



ROHS Conform

Data sheet**Industrial Ethernet
IE-BSS-V14M-SCRJ-MM-C**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings**Installation cut-out**