mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Order No.1058800000Part designationWTW ENVersionModular terminal, accessories, end plate and intermediate plate, dark beige, 3 mmEAN4008190140175Qty.20 pc(s).Additional technical dataTS 35 + TS 32UL 94 flammability rating of insulation materialV0DimensionsV0Width3 mmHeight of lowest version62 mmLength86 mm	General ordering data	
Part designationWTW ENVersionModular terminal, accessories, end plate and intermediate plate, dark beige, 3 mmEAN4008190140175Qty.20 pc(s).Additional technical dataInstallation adviceTS 35 + TS 32UL 94 flammability rating of insulation materialV0DimensionsWidth3 mmHeight of lowest version62 mmLength86 mmEnd plateColourdark beigeFunctionPartition plateHeight62 mmLength86 mmSnap-onYesUL 94 flammability rating of insulation materialV0Colourdark beigeFunctionPartition plateHeight62 mmLength86 mmSnap-onYesUL 94 flammability rating of insulation materialV0DownloadsStEPSTEP1058800000_12199_WTW_EN_STP.stpClassificationsEC000886ETIM 2.0EC000886ETIM 3.0EC000886eClass 4.127-14-11-99		1058800000
Version Modular terminal, accessories, end plate and intermediate plate, dark beige, 3 mm EAN 4008190140175 Qty. 20 pc(s). Additional technical data Installation advice Installation advice TS 35 + TS 32 UL 94 flammability rating of insulation material V0 Dimensions V0 Width 3 mm Height of lowest version 62 mm Length 86 mm End plate Colour Colour dark beige Function Partition plate Height 62 mm Length 86 mm Snap-on Yes UL 94 flammability rating of insulation material V0 Downloads Yes STEP 1058800000_12199_WTW_EN_STP.stp Classifications EriM 2.0 ETIM 2.0 EC000886 ETIM 3.0 EC000886 eClass 4.1 27-14-11-99		
intermediate plate, dark beige, 3 mmEAN4008190140175Qty.20 pc(s).Additional technical dataInstallation adviceTS 35 + TS 32UL 94 flammability rating of insulation materialV0DimensionsWidth3 mmHeight of lowest version62 mmLength86 mmEnd plateColourdark beigeFunctionPartition plateHeight62 mmLength86 mmSnap-onYesUL 94 flammability rating of insulation materialV0DownloadsV0ClassificationsV0ETIM 2.0EC000886ETIM 3.0EC000886eClass 4.127-14-11-99		
EAN4008190140175Qty.20 pc(s).Additional technical dataInstallation adviceTS 35 + TS 32UL 94 flammability rating of insulation materialV0DimensionsWidth3 mmHeight of lowest version62 mmLength86 mmEnd plateColourdark beigeFunctionPartition plateHeight62 mmLength86 mmSnap-onYesUL 94 flammability rating of insulation materialV0DownloadsYesSTEP105880000_12199_WTW_EN_STP.stpClossificationsEC000886ETIM 2.0EC000886ETIM 2.0EC000886eclass 4.127-14-11-99	VEISION	
Qty. 20 pc(s). Additional technical data TS 35 + TS 32 UL 94 flammability rating of insulation material V0 Dimensions V0 Width 3 mm Height of lowest version 62 mm Length 86 mm End plate Colour Function Partition plate Height 62 mm Length 86 mm Snap-on Yes UL 94 flammability rating of insulation material V0 Downloads V0 STEP 1058800000_12199_WTW_EN_STP.stp Classifications EC000886 ETIM 2.0 EC000886 ETIM 2.0 EC000886 ETIM 3.0 EC000886 eClass 4.1 27-14+11-99	EAN	
Additional technical data Installation advice TS 35 + TS 32 UL 94 flammability rating of insulation material V0 Dimensions Vidth Width 3 mm Height of lowest version 62 mm Length 86 mm End plate Colour Colour dark beige Function Partition plate Height 62 mm Length 86 mm Snap-on Yes UL 94 flammability rating of insulation material V0 Downloads V0 StEP 1058800000_12199_WTW_EN_STP.stp Classifications EC000886 ETIM 2.0 EC000886 ETIM 3.0 EC000886 eClass 4.1 27-14-11-99		
Installation adviceTS 35 + TS 32UL 94 flammability rating of insulation materialV0Dimensions3 mmWidth3 mmHeight of lowest version62 mmLength86 mmEnd plateColourdark beigeFunctionPartition plateHeight62 mmLength86 mmSnap-onYesUL 94 flammability rating of insulation materialV0DownloadsETIM 2.0EcolosesEcolose86ETIM 2.0EC000886ETIM 3.0EC000886eclass 4.127-14-11-99	Gty.	20 pc(3).
Installation adviceTS 35 + TS 32UL 94 flammability rating of insulation materialV0Dimensions3 mmWidth3 mmHeight of lowest version62 mmLength86 mmEnd plateColourdark beigeFunctionPartition plateHeight62 mmLength86 mmSnap-onYesUL 94 flammability rating of insulation materialV0DownloadsETIM 2.0EcolosesEcolose86ETIM 2.0EC000886ETIM 3.0EC000886eclass 4.127-14-11-99	Additional technical data	
UL 94 flammability rating of insulation material V0 Dimensions 3 mm Width 3 mm Height of lowest version 62 mm Length 86 mm End plate 2000000000000000000000000000000000000		TS 35 + TS 32
Dimensions Width 3 mm Height of lowest version 62 mm Length 86 mm End plate Colour Colour dark beige Function Partition plate Height 62 mm Length 86 mm Snap-on Yes UL 94 flammability rating of insulation material V0 Downloads STEP STEP 1058800000_12199_WTW_EN_STP.stp Classifications EC000886 ETIM 2.0 EC000886 ETIM 3.0 EC000886 eClass 4.1 27-14-11-99		
Width3 mmHeight of lowest version62 mmLength86 mmEnd plateColourdark beigeFunctionPartition plateHeight62 mmLength86 mmSnap-onYesUL 94 flammability rating of insulation materialV0OwnloadsSTEP105880000_12199_WTW_EN_STP.stpClassificationsEC000886ETIM 2.0EC000886ETIM 3.0EC000886eClass 4.127-14-11-99		
Height of lowest version62 mmLength86 mmEnd plateColourdark beigeFunctionPartition plateHeight62 mmLength86 mmSnap-onYesUL 94 flammability rating of insulation materialV0DownloadsSTEP105880000_12199_WTW_EN_STP.stpClassificationsETIM 2.0EC000886ETIM 3.0EC000886ETIM 3.0EC000886eClass 4.127-14-11-99	Dimensions	
Length86 mmEnd plateColourdark beigeFunctionPartition plateHeight62 mmLength86 mmSnap-onYesUL 94 flammability rating of insulation materialV0DownloadsSTEP105880000_12199_WTW_EN_STP.stpClassificationsETIM 2.0EC000886ETIM 3.0EC000886eClass 4.127-14-11-99	Width	3 mm
End plate dark beige Function Partition plate Height 62 mm Length 86 mm Snap-on Yes UL 94 flammability rating of insulation material V0 Downloads STEP 1058800000_12199_WTW_EN_STP.stp Classifications ETIM 2.0 EC000886 ETIM 3.0 EC000886 eClass 4.1 27-14-11-99	Height of lowest version	62 mm
Colourdark beigeFunctionPartition plateHeight62 mmLength86 mmSnap-onYesUL 94 flammability rating of insulation materialV0DownloadsClassificationsETIM 2.0EC000886ETIM 3.0EC000886eClass 4.127-14-11-99	Length	86 mm
Colourdark beigeFunctionPartition plateHeight62 mmLength86 mmSnap-onYesUL 94 flammability rating of insulation materialV0DownloadsClassificationsETIM 2.0EC000886ETIM 3.0EC000886eClass 4.127-14-11-99		
FunctionPartition plateHeight62 mmLength86 mmSnap-onYesUL 94 flammability rating of insulation materialV0DownloadsClassificationsETIM 2.0EC000886ETIM 3.0EC000886eClass 4.127-14-11-99		
Height62 mmLength86 mmSnap-onYesUL 94 flammability rating of insulation materialV0DownloadsSTEP105880000_12199_WTW_EN_STP.stpClassificationsETIM 2.0EC000886ETIM 3.0EC000886eClass 4.127-14-11-99	Colour	
Length86 mmSnap-onYesUL 94 flammability rating of insulation materialV0DownloadsSTEP1058800000_12199_WTW_EN_STP.stpClassificationsETIM 2.0EC000886ETIM 3.0EC000886eClass 4.127-14-11-99	Function	
Snap-onYesUL 94 flammability rating of insulation materialV0Downloads105880000_12199_WTW_EN_STP.stpClassificationsEC000886ETIM 2.0EC000886ETIM 3.0EC000886eClass 4.127-14-11-99		-
UL 94 flammability rating of insulation material V0 Downloads STEP 105880000_12199_WTW_EN_STP.stp Classifications ETIM 2.0 EC000886 ETIM 3.0 EC000886 eClass 4.1 27-14-11-99	•	
Downloads STEP 105880000_12199_WTW_EN_STP.stp Classifications ETIM 2.0 EC000886 ETIM 3.0 EC000886 eClass 4.1 27-14-11-99		
STEP 105880000_12199_WTW_EN_STP.stp Classifications ETIM 2.0 ETIM 3.0 EC000886 eClass 4.1 27-14-11-99	UL 94 flammability rating of insulation material	V0
STEP 105880000_12199_WTW_EN_STP.stp Classifications ETIM 2.0 ETIM 3.0 EC000886 eClass 4.1 27-14-11-99		
Classifications ETIM 2.0 EC000886 ETIM 3.0 EC000886 eClass 4.1 27-14-11-99		
ETIM 2.0 EC000886 ETIM 3.0 EC000886 eClass 4.1 27-14-11-99	STEP	1058800000_12199_WTW_EN_STP.stp
ETIM 2.0 EC000886 ETIM 3.0 EC000886 eClass 4.1 27-14-11-99		
ETIM 3.0 EC000886 eClass 4.1 27-14-11-99		E000000
eClass 4.1 27-14-11-99	-	
CUIdSS 3.0 Z1-14-11-33		
eClass 5.1 27-14-11-33		
	EC1035 J. 1	27-14-11-00



Similar products

Order No

Part designatio

Version

