

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

			REVISIONS	
REV	DESCRIPTION	DATE	APPROVED	
070	SEE ECN 93-0041-1	3/31/93	PCV	3/25/93
RECOMMENDED MOUNTING				
DESIGNED FOR USE WITH .141 DIA SEMI-RIGID CABLE CABLE ENTRY DIAMETER MINIMUM				
HOUSING .144				
CONTACT .037				
ELECTRICAL	MECHANICAL	ENVIRONMENTAL		
RF Leakage (dB MIN) (Interface Only, Fully Mated) -90-f(GHz)	Interface Dimensions DESC SPEC 85071	Temperature Rating -65° to +125°C Vibration MIL-STD-202, Method 204, Condition D Shock MIL-STD-202, Method 213, Condition I Thermal Shock MIL-STD-202, Method 107, Condition B Moisture Resistance MIL-STD-202, Method 106	INNER HOUSING BUSHING OUTER HOUSING SPRING WASHER DIELECTRIC CENTER CONTACT CONTACT SLEEVE CONTACT RING SHIM RETAINING RING SPRING WASHER	
			STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303 STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303 TFE FLUOROCARBON PER ASTM-D-1457 BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	
			GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290 PASSIVATE PER ASTM-A380 N/A GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550 GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290 GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550 NICKEL PLATE PER QQ-N-290 OVER COPPER PLATE PER MIL-C-14550 NICKEL PLATE PER QQ-N-290	
Corona, 70,000 Ft (VRMS MIN) 375 Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1500 Contact Resistance (Milliohms MAX) Center Contact 2.0 Outer Contact 2.0 Cable to Housing 0.5 RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 1000 IR.(Megohms MIN) 5000	Center Contact Captivation Axial (Lbs) 6 Cable Retention Axial Force (Lbs MIN) 60 Torque (In-Oz MIN) 55 Weight (Grams) 5.4	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± 1° DRAWN BY PCV 2-18-82 CHECKED BY G.A.L. 6-4-82 APPD BY R.M.F. 6-4-82 These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	COMPONENT MATERIAL FINISH	
			AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599	
CUSTOMER DRAWING AMP PART # 1059453-1 SHEET 1 OF 1 REV A				