

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








Amphenol

Micro SD to Mini SD adapter



Part Number:106-00330-**
Micro SD to Mini SD Adapter

- With Latch in card slot to prevent memory card slip
- Manufactured by insert-molding
- Application for bundle sales with micro SD memory card or CE devices

1.Materials:

Housing: High temperature thermoplastic,

UL 94V-0 rated. Contact: Copper alloy

Latch: Stainless steel SUS304

2.Contact finish:

Selective 5~15u" gold plating on contact area,

over nickel plating (50u"min)

3. Electrical specifications: Voltage Rating: 100VAC

Current Rating: 1A per contact

Dielectric strength: 500VAC initial and 250VAC

final for one minute

Insulation Resistance: $500M\Omega$ min at 500VDC Contact Resistance: $140m\Omega$ max at 100mA Operating temperature: $-25^{\circ}C^{-}+85^{\circ}C$

4.Mechanical specifications: Durability: 10000cycles. Mating force: 4N max Unmating force: 1N min

5.RoHS Compliant

