



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
02 ₂₁	REVISED PER ECN 99-0001	DM 5/13/99	S. Morby 5/18/99



NOTES

1. CONNECTOR CENTERLINES SHALL BE ALIGNED AS SHOWN ±30° FOR LENGTHS 165 MILLIMETER OR LESS. LENGTHS ABOVE 165 MILLIMETER SHALL HAVE CONNECTOR CENTERLINES ALIGNED AT RANDOM.

OUTER CONTACT	BERYLLIUM COPPER	GOLD PLATE
CENTER CONTACT	BERYLLIUM COPPER	GOLD PLATE
DIELECTRIC	POLYPROPYLENE, GF	N/A
CABLE: JACKET	POLYVINYLCHLORIDE	N/A
SHIELD	TINNED COPPER WIRE, 38 AWG	N/A
DIELECTRIC	FLUORINATED ETHYLENE PROPYLENE (FEP)	N/A
CENTER CONDUCTOR	TINNED COPPER CLAD STEEL	N/A

ELECTRICAL

Frequency DC - 6 GHz
 Nominal Impedance 50 ohms
 Voltage Rating 250 Volts (VRMS Max.) @ Sea Level
 VSWR 1.20:1 Max. @ 2GHz
 1.40:1 Max. @ 6GHz
 Insulation Resistance 1,000 Megohms Minimum
 Dielectric Withstanding Voltage 500 Volts (VRMS Minimum) @ Sea Level

MECHANICAL

Connector Durability 100 mating cycles

ENVIRONMENTAL

Temperature Rating -40°C (-40°F) To +105°C (221°F)

COMPONENT	MATERIAL	FINISH
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM TOLERANCE ON FRAC DEC ANGLES ± 1/64 ± 0.13 ± 1°		
DRAWN BY P. RESNICK DATE 24 MAY 91 CHECKED BY APPD BY [Signature] 05/13/92		AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
USE ASSY PROCEDURE NO. A.P. N/A		TITLE OSMT RIGHT ANGLE JACK TO JACK CABLE ASSEMBLY
SIZE B	CODE IDENT NO. 26805	9950-1305-23
SCALE 10:1		REV 02 ₂₁
		SHEET 1 OF 1