



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



AP VSSC6 LB**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



End plates (AP) for the VSSC product series in light blue and black

General ordering data

Order No.	1067230000
Type	AP VSSC6 LB
Version	Surge protection for instrumentation and control
GTIN (EAN)	4032248999866
Qty.	50 pc(s).

AP VSSC6 LB**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data**Dimensions and weights**

Width	1.5 mm	Height	88.5 mm
Depth	81 mm	Net weight	5.8 g

Temperatures

Humidity	5...96 %	Operating temperature	-40 °C...+70 °C
Storage temperature	-40 °C...+80 °C		

General data

Colour	Light Blue	Protection degree	IP 20
UL 94 flammability rating	V-0		

technical data

Colour	Light Blue	Humidity	5...96 %
--------	------------	----------	----------

Classifications

UNSPSC	30-21-18-11	eClass 4.1	27-14-11-27
eClass 5.1	27-14-11-27	eClass 6.2	27-14-02-01
eClass 7.1	27-14-11-33		

Approvals

Approvals