imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





ReSpeaker Mic Array - Far-field w/ 7 PDM Microp SKU 107010001


Far-field Voice Capture Acoustic Source Localization Beamforming Noise Suppression De-reverberation Acoustic Echo Cancellation




Description




The ReSpeaker Mic Array can be stacked (connected) right onto the top of ReSpeaker Core to significantly improve the voice interaction experience. It is developed based on the XVSM-2000 Smart Microphone from XMOS. The board integrates 7 PDM microphones to help enhance ReSpeaker's acoustic DSP performance to a much higher level. With the Mic Array attached onto the top of the ReSpeaker Core, ReSpeaker is now able to:





De-reverberation

Acoustic Echo Cancellation



XMOS microcontroller with 16 cores inside

7 high performance digital microphones

Supports Far-field Voice Capture (up to 10m)

Supports Beamforming, Acoustic Source Localization, Nosie Suppression, De-reverberation and Acoustic Echo Cancellation

12 programmable RGB LED indicators

Microphones: ST MP34DT01-M

Sensitivity: -26 dBFS (Omnidirectional)


Acoustic overload point: 120 dBSPL

SNR: 61 dB

Power Supply: 5V DC from Micro USB or expansion header

Dimensions: 70mm (Diameter)

Weight: 15.25g



1x ReSpeaker Far-filed Mic Array

Copyright © 2008-2016 Seeed Development Limited All rights reserved