# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## **HDC** enclosures **HDC IP68 24B TSS 1PG29**



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





The new RockStar® enclosures are resistant to seawater and offer a high degree of shock resistance, meet IP 68 and IP 69K, and have been developed for use under extreme environmental conditions and designed for the high vibration requirements acc. to DIN EN 61373 cat. 2 (bogie). As such, this housing family is ideally suited for fault- and maintenance-free operation of heavy-duty connectors in transport and traffic engineering as well as in power engineering and in applications with extreme requirements. During development, measures were also implemented to make the enclosures extremely EMCresistant.

#### **General ordering data**

Order No.	<u>1083000000</u>
Туре	HDC IP68 24B TSS 1PG29
Version	HDC enclosures, Size: 8, Protection degree: IP 68, Plug housing, Screw plug, Standard, Size of cable entries: PG 29
GTIN (EAN)	4032248846634
Qty.	1 pc(s).

## HDC enclosures HDC IP68 24B TSS 1PG29

## **Technical data**




### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Temperatures     Continuous operating temp., min.   -50 °C   Continuous operating temp., max     Dimensions   Total length housing   191 mm   Width housing C     Height of housing B   110.5 mm   Cable entry	58 mm 660 g x. 125 °C 58 mm w. threading
Height   110.5 mm   Net weight     Temperatures   Continuous operating temp., min.   -50 °C   Continuous operating temp., max     Dimensions   Total length housing   191 mm   Width housing C     Height of housing B   110.5 mm   Cable entry	660 g x. 125 °C 58 mm
Temperatures     Continuous operating temp., min.   -50 °C   Continuous operating temp., max     Dimensions     Total length housing   191 mm   Width housing C	x. 125 °C 58 mm
Dimensions   Total length housing 191 mm   Height of housing B 110.5 mm	58 mm
Total length housing191 mmWidth housing CHeight of housing B110.5 mmCable entry	
Height of housing B 110.5 mm Cable entry	
Height of housing B 110.5 mm Cable entry	
General data	_
Housing main material diecast aluminium	
Version	
Design of housing Plug housing Size	8
Design Standard Top part/bottom part/lid	upper part
Design of locking system Screw plug Cable entry	w. threading
Size of cable entries PG 29 Number of cable entry on top	0
Number of cable entry sideways 1	
Classifications	
ETIM 2.0 EC000437 ETIM 3.0	EC000437
UNSPSC 30-21-18-01 eClass 4.1	27-14-08-05
eClass 5.1 27-14-34-19 eClass 6.2	27-14-08-05
eClass 7.1 27-14-05-15	27 17 37 13
Approvals	
Approvals	
ROHS Conform	

## HDC enclosures HDC IP68 24B TSS 1PG29

## Drawings





## Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com