



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




HG 2320 ESD

Technical Specifications

Voltage:	120 VAC / 60 Hz
Power:	1600 watts
Amps:	13.3
Surface conductivity:	10 ⁴ ohms
Temperature	120 – 1200 °F (50 – 650 °C)
Airflow rate:	4 – 13 cfm. (continuously variable)
Stages:	2 (continuously variable)
Highlights:	Higher durability (+20 %), optimized weight balance, LCD-Display, 4 settings programmable, heat build-up warning, hanging ring, easily replaceable power cord, residual heat indicator, optional temperature scanner and fine dust filter
Power cord:	Industrial grade rubber, length: 6ft
Motor:	Brush motor
Heating element:	Ceramic heating element
Motor lifetime:	1000h
Accessories:	Use of our standard accessories
Dimensions:	9.96" x 3.41" x 7.87" (l x w x h)
Net Weight:	2.19 lbs (35.1 oz)
Single Sell Pack:	Dimensions: 10.20" x 3.54" x 9.33" Weight: 2.60 lbs (41.66 oz)
Country of origin:	Romania
Warranty:	One year limited



UPC-Code	Prod. No.
018139256977	110025697



RoHS
Compliant



double insulated

ISO
9001:
2015
14001:
2015

Product data sheet

HG 2320 ESD

The HG 2320 ESD is an ESD-compliant hot air tool and fulfills the requirements of IEC DIN EN 61340-5-1; part 5-1:2008 ff.

The HG 2320 ESD has a housing surface conductivity of 10^4 ohms and is suitable for use in electrostatic protected areas. The conductive housing will not build up or hold static charge when used in an EPA (ESD protected area).

Notice: This hot air tool has no protective conductor terminal to ground. The electrical discharge is through the hand of the (grounded) user or through the deposit of the hot air tool on an ESD-compliant work area.

STEINEL
PROFESSIONAL

ESD-AKADEMIE[®]

PRODUCT CERTIFICATE

the

ESD-Akademie hereby certifies that the product / model

Hot air tool for industrial applications

Series "HG 2320 E"

of the manufacturer

STEINEL[®]

Steinel GmbH

Dieselstraße 80-84

D-33442 Herzebrock-Clarholz / Germany

according to the results of a product sample test, documented in a report, complies with the

**requirements for handling of ESD sensitive products (ESDS)
and for using in ESD protection areas (EPA) in accordance
with the Standard**

IEC 61340-5-1

(Edition 2007-08)

IEC DIN EN 61340-5-1

(Edition July 2008 / draft June 2011)

fulfilled.

This product certificate confirms the quality of the tested product sample.

The manufacturer is responsible for permanently production monitoring and quality assurance.

Certificate-Registration-No.: ESD-PZ-51026010-ST-HG2320E

Großmaiseid, 4th January 2017


Michael Böhm
managing Director


Torsten Röder
academy manager



ESD-Akademie[®] | Industriestraße 27 | D-56276 Großmaiseid
www.esd-akademie.de | Observe Copyright ISO 16016