



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



HB 1750

Professional Heat Blowers

STEINEL[®]
PROFESSIONAL



 Double Insulated



HB 1750 Specifications

Item No.	HB 1750 34750 (includes all 5 keys) HB 1750 B 34751 (blower w/ blue key) HB 1750 G 34752 (blower w/ gray key) HB 1750 Y 34753 (blower w/ yellow key) HB 1750 O 34754 (blower w/ orange key) HB 1750 R 34755 (blower w/ red key)
Temperature	200°F - 1200°F (95°C - 650°C) all 5 keys
Airflow	up to 23 cfm, adjustable with baffle
Element	plug-in heating element
Output	1750 watts
Voltage	120 VAC / 50/60 Hz
Amps	14.6
Power Cord	industrial grade rubber, length: 6 ft
Nozzle Diameter	1.7" (43.5 mm)
Net Weight	2.9 lbs (46.4 oz)
Dimensions	10.8" x 5.8" x 9.5" (l x w x d)
Single Sell Pack	dimensions: 11.4" x 9.5" x 3.7" weight: 2.7 lbs (43.5 oz)
Warranty	one year limited
Certifications	C-UL-UL Listed, RoHs Compliant, ISO 9001:2001 Made in E.U.

HB 1750 Professional Heat Blower

The HB 1750 has been specifically optimized for drying efficiency and for heat-shrinking tubes and sleeves on thick cables.

This extremely powerful heat tool delivers almost 30% more air than conventional tools. Continuously adjustable airflow ensures the user stays in control.

The ergonomically shaped soft grip handle permits fatigue-free working. The included stand offers stationary operation at any angle.

Applications

Shrink wrapping, activating adhesives, softening compounds, window tinting, bending plastics and other applications requiring long life and even heat

Key Features:

- Powerful turbine blower with air delivery rate up to 23 cfm
- Color coded keys for the right temperature every time
- Maintenance free factory sealed motor
- Lightweight, well balanced design
- Soft grip handle with convenient slide switch (Off / Cool / Hot)
- Ultra quiet operation
- Plug-in heating element takes only seconds to change
- Quick-lock stand is fully adjustable and stores keys
- Available accessories enhance versatility



Adjustable Stand




Baffle Adjusts Air and Temperature within Range



Cool Air Stage



Quick and Easy Field Changeable Element



Plug-In Heating Element



www.steinell.net

HB 1750

Professional Heat Blowers



Industry Specific Kits Available



HB 1750 Kit

- Quick Lock Stand
- 5 Temperature Keys
- Large Reflector
- Spare Element
- Silver Case

No. 34759



Color coded keys each lock in a specific temperature range

Model	Color	°F / °C
HB1750	Red, Orange, Yellow, White, Blue	200-1200°F (95-650°C)
HB 1750 B	Blue	200-300°F (95-150°C)
HB 1750 G	White	300-500°F (150-260°C)
HB 1750 Y	Yellow	500-750°F (260-400°C)
HB 1750 O	Orange	750-1000°F (400-540°C)
HB 1750 R	Red	1000-1200°F (540-650°C)

Accessories for a Variety of Applications



7 mm Reducer
2.5" x 1.8" x 1.8"
No. 07695



200 mm Spreader
7.9" x 6.0" x 1.8"
No. 07725



40 mm Large Reflector
5.9" x 2.6" x 1.8"
No. 07705



20 mm Small Reflector
4.1" x 1.8" x 1.8"
No. 07715



Heating Element
4.1" x 1.8" x 1.8"
No. 06110