



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





# Me Flame Sensor

SKU: 11036 Weight: 8.00 Gram

## Description :

Me Flame Sensor can be used to detect fire source or light source with wavelength in the range of 760 nm to 1100 nm. Its detection angle is up to 60 degrees, and detection accuracy can be adjusted. When the flame is detected, its blue indicator will light on. It can be applied to the safety monitoring projects such as fire-fighting robot and flame alarm. The port of this module has black ID, and RJ25 cable can be used to connect to the port with black ID on Makeblock Orion.

## Features:

- The detection distance is 1m when the height of flame is 5cm;
- The onboard potentiometer can be adjusted for its sensitivity;
- Anti-reverse protection - connecting the power supply inversely will not damage IC;
- White area of module is the reference area to contact metal beams;
- Adopt RJ25 port for easy connection;
- Provide output ports for digital and analog signal;
- Provide pin-type of port to support most development boards including Arduino series.

## Specification:

- Operating voltage: 5V DC;
- Spectrum band detected: 840-1200nm;
- Detection angle: 60°;
- Feedback time: 15 $\mu$ s;
- Control mode: digital and analog port;
- Operating temperature: -25°C~80°C / -13°F~176°F (Don't be too close to the flame to prevent from damage) ;
- Module dimension: 51 x 24 x 18mm (L x W x H)

## Size Chart:

Height/Width/Length: 51 x 24 x 18mm (2 x 1 x 0.7inch)

## Part List:

1 x Me Flame Sensor





<https://store.makeblock.com/me-flame-sensor> 8-6-18