



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SW 2007				符号×数 Part		変更事項 Revision Record		担当者 Changed		日付 Date		確認 Checked		日付 Date		承認 Approved		日付 Date																			
				<table><tr><td>型番 Product Code</td><td>材質 Material</td><td>色 Color</td><td>結束後使用温度範囲 Temperature Range (After Bundle)</td><td colspan="2">UL</td></tr><tr><td>T50R-TZ</td><td>ふっ素樹脂 耐熱・耐薬品 ／ETFE Heat Stabilized & Chemical resistance</td><td>青色 Blue</td><td>-80℃～+170℃</td><td>主原料 Material</td><td>製品 Product</td></tr><tr><td></td><td></td><td></td><td></td><td>UL94V-0</td><td>E64962</td></tr></table>																型番 Product Code	材質 Material	色 Color	結束後使用温度範囲 Temperature Range (After Bundle)	UL		T50R-TZ	ふっ素樹脂 耐熱・耐薬品 ／ETFE Heat Stabilized & Chemical resistance	青色 Blue	-80℃～+170℃	主原料 Material	製品 Product					UL94V-0	E64962
				型番 Product Code	材質 Material	色 Color	結束後使用温度範囲 Temperature Range (After Bundle)	UL																													
				T50R-TZ	ふっ素樹脂 耐熱・耐薬品 ／ETFE Heat Stabilized & Chemical resistance	青色 Blue	-80℃～+170℃	主原料 Material	製品 Product																												
				UL94V-0	E64962																																
<table><tr><td>L</td><td>T</td><td>A</td><td>B</td><td>C</td><td>D</td></tr><tr><td>201.0±2.0</td><td>1.5±0.2</td><td>4.7±0.2</td><td>9.0±0.2</td><td>6.0±0.2</td><td>8.8±0.2</td></tr></table>						L	T	A	B	C	D	201.0±2.0	1.5±0.2	4.7±0.2	9.0±0.2	6.0±0.2	8.8±0.2																				
L	T	A	B	C	D																																
201.0±2.0	1.5±0.2	4.7±0.2	9.0±0.2	6.0±0.2	8.8±0.2																																
結束径／Bundle Diameter																																					
φ5～φ50																																					
ループ引張強度(最小値) ／Min. Loop Tensile Strength																																					
222.3N																																					
寸法単位／Dimension Units																																					
mm																																					
性能 仕様		／ Performance ／ Specification																																			
<p>本製図の版權はヘルマンタイトン(株)に属し事前の書面での許可無く第三者にもらしたり複写することを禁ずる。</p> <p>The copyright of this drawing is reserved by HELLERMANN TYTON. It is issued on condition that it is not reproduced, copied or disclosed to a third party, either wholly or in part, without the consent of HELLERMANN TYTON.</p>				製図／Drawn		15/02/2010		S. Yokoyama		尺度 / Scale				2 : 1																							
				承認／Approved		15/02/2010		T. Takagaki		製品名/型番 / Title																											
										スタンダードタイ / T50R-TZ STANDARD TIE																											
										UNS No. 111-00732				用紙 A4 D. Size																							
						図面番号/Drawing-No. 10047-13-401								ページ 1/1 Sheet																							

XCT-TCJ040CST