



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



111-01332

Article Number: 111-01332



Download drawing

Download spec sheet

Base Data

Local Order Number	111-01332
Type	T120R
Color	Red (RD)
Features and Benefits	HellermannTyton manufactures a full line of high quality cable ties in a variety of styles, sizes, materials, and colors. HellermannTyton cable ties are engineered and manufactured for maximum performance and quality.
Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Product Dimensions

Minimum Tensile Strength (Imperial)	120.0 lbs
Minimum Tensile Strength (Metric)	535.0 N
Length L (Imperial)	15.2 "
Length L (Metric)	387.0 mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.3 "
Width W (Metric)	7.4 mm
Bundle Diameter Min. (Imperial)	0.59 "
Bundle Diameter Min. (Metric)	15.0 mm
Bundle Diameter Max. (Imperial)	4.1 "
Bundle Diameter Max. (Metric)	105 mm

Logistics and Packaging

Package Quantity (Metric)	50
---------------------------	----

Material and Specifications

Material	Polyamide 6.6 (E/CTFE)
Material Shortcut	PA66E/CTFE
Flammability	UL94 V0

**Operating Temperature** -103°F to +302°F (-75°C to +150°C)

**ROHS Compliant** Yes

**UL Recognized (US and Canada)** Yes