



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**Device markers
CC 15/45 MC NE GE**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The **CC 15/45 MC** is ideal for the 45-mm wide contactor relays and motor circuit breakers. It provides a clean, large-area identification in the electrical cabinet. Can be mounted either as a self-adhesive variant or using a CC-rail 1000 tag rail

General ordering data

Order No.	1111230000
Type	CC 15/45 MC NE GE
Version	Device markers, MultiCard, 15 x 45 mm, Polyamide 66, Colour: Yellow
GTIN (EAN)	4032248888757
Qty.	40 pc(s).

**Device markers
CC 15/45 MC NE GE**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Length	15 mm	Width	45 mm
Height	1.2 mm	Net weight	2.6 g

Markings

Cadmium	No	Can be labelled with thermal transfer printers	No
Can be printed with plotter	Yes	Can be written with dot-matrix printer	No
Can be written with laser printer	No	Colour	Yellow
Conductor O.D.		Halogen	No
Material	Polyamide 66	Material colour according to resistance code	4
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Pin can be written (STI)	Yes	PrintJet	Yes
Silicone	No	Speed marking laser	Yes
UL 94 flammability rating	V-2		

Classifications

ETIM 2.0	EC001288	ETIM 3.0	EC001288
UNSPSC	30-21-18-01	eClass 4.1	24-19-02-18
eClass 5.1	27-14-91-29	eClass 6.2	27-14-91-29
eClass 7.1	27-14-91-29		

Product information

Description of article	MultiCard markers for labelling devices
------------------------	---

Approvals


Approvals	
ROHS	Conform

**Device markers
CC 15/45 MC NE GE**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Example of use



Product is similar to illustration