



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



HDC insert HDC HP 550 M 150

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



A heavy-duty connector consists of a connector insert and its protective housing. The insert is therefore the heart of the heavy-duty connector. It is responsible for electrical functioning. Connector inserts from Weidmüller are made from high-quality insulation materials, which allow secure transmission of high voltages in a tight space. Moreover, we use only a single type of plastic in our entire product line. This plastic is UL listed, and suitable for railway applications. This allows unlimited world-wide use of the RockStar® connector.

General ordering data

Order No.	1119110000
Type	HDC HP 550 M 150
Version	HDC insert, Male, 3000 V, 550 A, Crimp connection, Size: 550
GTIN (EAN)	4032248900367
Qty.	1 pc(s).

HDC insert HDC HP 550 M 150

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Length	91 mm	Net weight	125 g
Diameter	43 mm		

General data

Size	550	Series	HighPower
Rated voltage (DIN EN 61984)	3,000 V	Rated impulse voltage (DIN EN 61984)	15 kV
Rated current (DIN EN 61984)	550 A	UL 94 flammability rating	V-0
Insulation resistance	10 ¹⁰ Ω	Insulating material	Polyamide with fibre optic
Conductor cross-section	150 mm ²	Pollution severity	PD 2 (PD 3)
Type	Male		

Connection data PE

Wire connection cross section AWG, max.	kcmil 250	Connection type PE	Screw connection
---	-----------	--------------------	------------------

Rating data

Rated current (DIN EN 61984)	550 A	Rated impulse voltage (DIN EN 61984)	15 kV
Rated voltage (DIN EN 61984)	3,000 V		

Version

Wire connection cross section AWG, max.	kcmil 250	Stripping length, rated connection	30 mm
Type of connection	Crimp connection	Size	550
Volume resistance	≤ 0.1 mΩ	Surface finish	Silver passivated
Material	Copper alloy		

Classifications

ETIM 2.0	EC000796	ETIM 3.0	EC000796
UNSPSC	30-21-18-01	eClass 4.1	27-14-08-05
eClass 5.1	27-14-34-19	eClass 6.2	27-14-34-19
eClass 7.1	27-44-02-05		

Product information

Descriptive text technical data	In the version described here, the crimp contacts can be used for crimp connections with flexible, stranded, and finely stranded copper wires (according to DIN 48201 part 1 and DIN 57 295 VDE 0295) or with crimping inserts (according to DIN 48083 part 1, part 3 and part 4). We are happy to provide crimp contacts to meet your requirements.
Descriptive text accessories	For further accessories, see chapter J - tools, see chapter K

Approvals

Approvals	
ROHS	Conform