



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



G1&2 Electric Solenoid Valve (Normally Closed)

SKU 111990004



Description

This is a normally closed G1/2 12VDC electric solenoid valves with barbed inlet and outlet ports, great for projects involving low viscosity fluid control. You can find it ubiquitous on applications like automatic faucets, foot operated faucets, drinking fountains etc.

We have also a counterpart product which is normally open. Check it out if it's more suitable to your need: [G1/2 Electric Solenoid Valve \(Normally Open\)](#).

Features

- Normally closed
- Durable
- Stainless steel inlet filter
- Wide operation temperature range

Specifications

- Working voltage: 12VDC
- Max current: 450mA
- Operating mode: normally closed
- Inlet/Outlet ports: G1/2"
- Materials: nylon/ stainless steel/Polyoxymethylene
- Valve type: diaphragm valve (operated by servo)
- Filter screen: stainless steel inlet filter
- Max operating temperature: 120°C
- Operating pressure range: 0.02 – 0.8 MPa
- Expected life: 200,000+