imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Brad® applicomIO Ethernet network interface cards provide powerful and reliable data acquisition for PC-based control and visualization applications.

Some of the world's most demanding high-speed control and automation applications run on standard PCs using Brad applicomIO network interface cards. Dedicated DCS and PLC systems have been eliminated in favor of open platforms running PC-based control systems.

The benefits include:

- Reduced material costs
- Reduced development times
- · More flexible and customizable systems • Reduced field-support costs

Brad applicom IO products have been designed for industrial applications independently of the fieldbus used. OEMs, system integrators and end-users can take advantage of developing standard control applications as well as selecting the fieldbus connectivity required from the applicomIO product range.

Brad applicomIO products consist of a fieldbus card and engineering tools which quickly and easily setup communication. Everything is included for a successful implementation at a lower cost.

Brad applicomIO network interface cards provide connectivity support for all popular fieldbuses including EtherNet/IP, PROFINET IO, Modbus TCP, PROFIBUS, DeviceNet and CANopen. Our cards are developed in compliance with the technical specifications of industrial organizations and comply with the applicable industrial standards. Brad applicomIO supports up to 8 cards in a single PC and can run on various operating systems including Windows 32-bits, Linux as well as real-time OS such as VxWorks, QNX, and VenturCom RTX.

Particularly, the Brad applicomIO network interface card provides high-speed deterministic communication to exchange data with industrial devices through Modbus Ethernet messaging. The built-in processor handles all the protocol management to offer reliable and outstanding performance.

The software package includes a common development library for all fieldbuses supported. The process data is exchanged with the control application through a shared memory where inputs/outputs are automatically mapped. To monitor the communication between the card and the control application, the library includes a watchdog feature to automatically detect software blocking.

A real Turnkey Solution

Brad applicomIO configuration software console provides a standardized and userfriendly environment for guick development of communication applications without the worry of knowing industrial communication protocols. The console saves time during the commissioning phase by offering features such as automatic device detection, user configuration management, diagnostic information, etc.

Product package includes:

- · Network interface card
- · Engineering console for configuration and diagnostic tools
- Data servers (OPC DA 3.0 & 2.05, DAServer, FastDDE/SuiteLink)

FEATURES AND BENEFITS

- Support of Windows 32-bit and 64-bit (WoW64)
- · Support of Windows Seven and 2008 Server
- Support of PCI Express 1x form factor
- Protocols:
 - Modbus TCP Client
 - Modbus UDP Client
- · Reliable solution based on embedded protocol technology for powerful data throughput

TYPICAL APPLICATIONS

- PC-Based Control
- · Robotic application
- Panel PC visualization system

- Development libraries:
- Windows (DLL), VenturCom (RTX) Static library for non-windows OS
- (VxWorks, QNX, Linux, etc)
- Single-time development of API for whatever fieldbus used
- "User-friendly" engineering tools for configuration and diagnostics
- Remote connection through Ethernet port (for embedded system platform)
- Application watchdog
- Automatic I/O mapping for easy configuration
- I/O exchange up to 14 Kbytes

Brad® applicomIO Modbus TCP Network Interface Card

112000 PCI Universal Bus and **PCI Express**

PCI 3.3/5V





MODBUS TCP



SUPPORTED OS

Standard package

- Windows 32-bit and 64-bit (WoW64)
 - Windows XP
 - Windows 2003 Server
 - Windows Vista
 - Windows Seven
 - Windows 2008 Server
 - Windows 2008 Server R2
- Other operating systems
 - Ardence RTX, VxWorks, QNX, Linux, DOS



SPECIFICATIONS

Technical Data

- Bus interface: PCI rev 2.2, 32-bit, 33 MHz, PCI Universal 3.3V/5V keying, PCI-X compatible PCI Express 1x
- Processor: AMD SC520 133 MHz
- Memory: SDRAM: 16 Mbytes Flash: 4 Mbytes
- Interruption: Hardware Plug&Play
- DPRAM Address: Hardware Plug&Play (32 Kbytes used per card)
- Dimensions (L x W): 168mm x 107mm (6.61" x 4.21")
- Consumption: 5.5 W
- Operating Temperature: 0°C (32°F) up to +65°C (149°F)
- Storage Temperature: -40°C (-40°F) up to +85°C (185°F)
- Discrete Input: 1x Opto-coupled
- Discrete Output: 1x "WatchDog" (dry contact)
- EMC Compliance: N55022 Class B, EN61000-6-2, EN61000-3-2, EN61000-3-3
- RoHS Compliance: YES

ORDERING INFORMATION

Engineering No.

DRL-EMB-PCU

DRL-EMB-PCIE

Order No.

112000-5029

112000-5034

Communication Port

- Port type:
- Ethernet port IEEE 802.3 for industrial applications
- Connector type: BaseT (RJ45)
- Speed: 10/100 Mbps (Auto-negotiation)
- LED indicators: 4 LEDs - TX, RX, Link, 100 Mbps
- Remote Access: Also usable for remote and diagnostic configuration

Protocol

- Connect Ethernet Modbus devices server according to Modbus-IDA specifications
- Support both TCP and UDP connection modes
- Up to 127 simultaneous devices

Product Description

PCU-ETHIO Ethernet card for Modbus TCP Client, PCI 3.3/5V


PCIE-ETHIO Ethernet card for Modbus TCP Client, PCI Express 1x

Brad® applicomIO Modbus TCP Network Interface Card

112000 PCI Universal Bus and PCI Express

SOFTWARE TOOLS

Brad® applicomIO software tools enable fast integration of the fieldbus into your control application. Independently from the fieldbus used, the console remains the same.




Configuration console

E APPLICOM OPCIer-e 1 E CAVO1 E DATABASE	1360° 1380° 1360° 1360°	-	C Rad
Syndous Bi Owanicus EQUIPHENTI COUNIENT2 III CARO2	1 2 3 3 5 5 5 5 5 5 5 5 5 1 5 5 5 1 5 5 5 1 5 5 5 1 5		G Al G Al F BOOL C DITE C dott C birts C b
Hend CHARTCHARTCHER Made If the IF terresticul Mend CARDITISATABADE SYMBOLSY CARDITISATABADE SYMBOLSY CARDITISATABADE SYMBOLSY	Add Add		(84)
			CIK.

OPC Browser



- Share	dime			
	ml.	VI V		
interes.				



Diagnostic and test tools

www.molex.com/link/applicomio_modbustcp.html