imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



| - | 12 | 1 [,] | 110 | 9 | 8 | 7 | 6 |
|-----------|---|-----------------------------------|--|---------------------------------|----------------------|---|---------------------------------------|
| | MATERIAL NUMBER | ENG NO. | DESCRIPTION | INSULATOR KEYING POSITION | HORSEPOWER RATING | | |
| н | 1122191001 | ARC30MA01 | ARC 30A M 125VAC 1P+N+G | | 1 HP | | 1.89 |
| | 1122191002 | ARC30MB02 | ARC 30A M 250VAC 2P+G | | 3 HP | | 48.0 |
| | 1122191003 | ARC30MB03 | ARC 30A M 250VAC 3P+G | - 7 | 5 HP | | |
| | 1122191004 | ARC30MAB04 | ARC 30A M 125/250VAC 2P+N+G | _ | NA | | |
| | 1122191005 | ARC30MC02 | ARC 30A M 208VAC 2P+G | | NA | Ī | |
| | 1122191006 | ARC30MC03 | ARC 30A M 208VAC 3P+G | 16 | 5 HP | | |
| F | 1122191007 | ARC30MAC05 | ARC 30A M 120/208VAC 3P+N+G | - | NA | 1.890 | |
| F | 1122191008 | ARC30MD01 | ARC 30A M 277VAC 1P+N+G | | NA | 48.00 | |
| G | 1122191009 | ARC30ME02 | ARC 30A M 480VAC 2P+G | - | NA | | |
| F | 1122191010 | ARC30ME03 | ARC 30A M 480VAC 3P+G | - 4 | NA | V | |
| | 1122191011 | ARC30MDE05 | ARC 30A M 277/480VAC 3P+N+G | - | NA | | |
| | 1122191012 | ARC30MF02 | ARC 30A M 600VAC 2P+G | | NA | | |
| | 1122191013 | ARC30MF03 | ARC 30A M 600VAC 3P+G | 14 | NA | / | |
| F | 1122191014 | ARC30MGF05 | ARC 30A M 347/600VAC 3P+N+G | - | NA | [.194] | |
| F | | L | 1 | | | \emptyset 4.93 — EARANCE FOR 8-32 FAS ⁻ | TENER |
| | | | | INSULATOR K | EYING INDICAT | OR | |
| | | | [1.319] ◄─── 33.50 ─ ─ ► | | | (2.047) | |
| | | | | | | (52.00) – | |
| E | | | | | | (52.00) | |
| | | | | | | | |
| | | 1 | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| D | | | | | | | |
| | (2.854) | S | | | | | |
| | (72.49) | | | | _ | | |
| | (72.49) | F | | | | | |
| | | ES . | | | | | |
| | | | | | | | |
| | | | SL 91 10 80 | | | | |
| С | | | | | | | |
| | | | | | | | |
| | <u> </u> | | | | | | |
| | | | | | | | |
| | NOTES: | | | | | | |
| | MATERIALS: | | | | | | |
| в | | | .TORS: GLASS FILLED PBT .LOY WITH A SILVER NICKEL TIP, SIL ^v | VER PLATED. | | | |
| | MOUN | NTING GASKET: SIL | | | | | |
| | RATING: CURR | RENT: 30 AMPS | | | | | SYMBC |
| | VOLT | AGE AND HORSEP | OWER: SEE TABLE | | | | F = |
| | OPERATING TEMPERATURE: -40°C (-40°F) TO 60°C (140°F) ENVIRONMENTAL: NEMA TYPE 4X | | | | | | |
| | | - | WG MIN. TO 8 AWG MAX. | | | | |
| | | | REWS TO 1.7 N-M (15 in/lbs) | | | | · · · · · · · · · · · · · · · · · · · |
| | AGEN | ICY: UL LISTING PE SWITCH RATE | ENDING ID INLET/PLUG | | | | ▼ = |
| Α | | BRANCH CIRC | UIT DISCONNECT SWITCH | | | | |
| | | MOTOR CIRCU | JIT DISCONNECT SWITCH IF HP RATE | <u>-</u> D | | | = |
| | THIS DRAWIN | G REPLACES SD-1 | 12219-101 | | | | |
| FOI | DOCUMENT STATUS | P1 RELEASE DATE | | 9 | 8 | 7 | <u> </u> |
| KE) DA | TE: 2017/02/06 | T | ı IV | 3 | 0 | 1 | 6 |



 \oplus \leftarrow

3

DOCUMENT NUMBER

1122191010

2

DOC TYPE DOC PART SHEET NUMBER

PSD 000

1 OF 1

1

MUST REMAIN

WITHIN DIMENSIONS

Δ

B2

5

0