



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





SIDEKICK,T & N

Sidekick T&N

Cat No: 1137-5002

UPC No: 783310605263

Description

- Five transmission and noisetests
- Determines the stressed noise susceptibility of dry and working pairs
- Measures resistance, AC/DCvolts, and capacitive kick
- Provides tone for twisted pair or crossed conductor identification
- Single setup for testing Tip-Ring, Tip-Ground, and Ring-Ground
- Minimal drying effect in all ranges
- Field replaceable leads
- Softcase with adjustable strand hook
- Low battery indicator light

Specifications

- AC Voltage : 0 - 300 V RMS
- Circuit Loss : -15 To +1 DB
- Circuit Noise : 0 To 75 DBRNC
- DC Voltage : 0 - 300 VDC
- Dimensions : 10.750 IN X 4.250 IN X 2.500 IN
- Leakage : RX10K: Reads 0 To 20 MOHM
- Loop Current : 0 - 100 MILAMP
- Power : Four AA batteries
- Power Influence : 50 - 100 DBRNC
- Replacement Part : 1134-1002S Case, 1131-0202 Test Leads
- Resistance : RX1: Reads 0 To 2000 OHM, RX1K: Reads 0 To 2 MOHM
- Storage/Operating Temperature : -4 To 140 DEG F
- Stress Test : 0 To 82 DBRNC
- Sub Brand : Sidekick
- Type : T And N Series
- Voltage Measurement :
 - 0 - 300 VDC
 - 0 - 300 VAC RMS
- Weight : 2.000 LB