



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





'118' SERIES AM REMOTE CONTROL SYSTEMS.

- Complete Remote Control System
- Range Up To 100 Metres
- 12 or 24Vdc Supply.
- Easy Installation Via Screw Terminals.
- 1 Relay Output 12Apk @ 230Vac
- 2 Relay Outputs 2A @ 12Vdc
- Momentary or Latching Outputs
- IP65 Rated Enclosure
- Wall Mounting Lugs Supplied
- Highly secure Keeloq protocol.
- 433MHz version CE Compliant for use in Europe
- 315MHz FCC Compliant for use in USA



Description

This remote control system is supplied ready to operate. Installation requires connections to power supply screw terminals and the output relay contacts.

Ordering Information

PART No	DESCRIPTION
118C1AR5	AM Remote control System 1 Channel, 433MHz
118C3AR5	AM Remote control System 3 Channel, 433MHz
118C1-315AR1	AM Remote control System 1 Channel, 315MHz
118C1-315AR1	AM Remote control System 3 Channel, 315MHz

Additional Transmitter Keyfobs

This remote control system is supplied ready to operate. Installation requires connections to power supply screw terminals and the output relay contacts.

PART No	DESCRIPTION
110C1-315	Transmitter Keyfob 1 switch, 315 MHz
110C2-315	Transmitter Keyfob 1 switch, 315 MHz
110C3-315	Transmitter Keyfob 3 switch, 315 MHz
AM-110C1-433	Transmitter Keyfob 1 switch, 433 MHz
AM-110C2-433	Transmitter Keyfob 2 switch, 433 MHz
AM-110C3-433	Transmitter Keyfob 3 switch, 433 MHz



'118' SERIES AM REMOTE CONTROL SYSTEMS.

Data Outputs

Each output relay provides an isolated switch. Connections are Common (COM), Normally Open (NO) and Normally Closed (NC). The jumper links (J1, J2) configure the outputs to be momentary or latching.

118C1 (1 switch keyfob)		
Link Status		Decoder Output
LK1(J1)	LK2(J2)	O/P 1
Open	Open	Latch
Open	Connected	Mom

118C3				
Link Status		Transmitter Switch (2 or 3 switch keyfob)		
		LH	RH	TOP
LK1(J1)	LK2(J2)	O/P 1	O/P2	O/P3
Open	Open	Latch	Latch	Latch
Open	Connected	Mom	Mom	Mom
Connected	Open	Mom	Mom	Latch
Connected	Connected	Latch	Latch	Mom

Learning A New Transmitter Keyfob Switch

1. Press the learn switch (SW1), the accept LED will illuminate.
2. Press the transmitter once, accept LED will extinguish.
3. Press the transmitter again, the accept LED will flash.
4. Wait for the accept LED to stop flashing.
5. This transmitter will now operate the system.

The system can learn upto 50 unique transmitter keyfobs



'118' SERIES AM REMOTE CONTROL SYSTEMS.

Technical Specifications

Storage Temperature; -10 to +70° Celsius. Operating Temperature; 0 to +55° Celsius.

Transmitter Keyfob

Battery Type GP23A

ELECTRICAL CHARACTERISTICS	MIN	TYPICAL	MAX	DIMENSION
Supply Voltage	8.5	9	16	V
Supply Current : Quiescent		0		mA
Supply Current : all relays operating		8		mA
Operating frequency				
315MHz Versions		315		MHz
433MHz Versions		433.92		MHz

Receiver / Decoder

Enclosure Dimensions 110 x 85 x 35mm

PCB Dimensions 74 x 68mm

ELECTRICAL CHARACTERISTICS	MIN	TYPICAL	MAX	DIMENSION
Supply Voltage for 24Vdc		24.0	30.0	V
Supply Voltage for 12Vdc	9	12.0	16.0	V
Supply Current :				
Quiescent		10		mA
All Relays operating		200		mA
Mains rated Relay Rating (230Vac)		5	12	A
Low voltage Relay Rating				
At 12Vdc			2	A
At 50Vdc			1	A

For more information or general enquiries, please call;

RF Solutions Ltd.,

Unit 21, Cliffe Industrial Estate,

Lewes, E. Sussex. BN8 6JL.

England.

Email : sales@rfsolutions.co.uk

<http://www.rfsolutions.co.uk>

Tel: +44 (0)1273 898 000 Fax: +44 (0)1273 480 661

RF Solutions is a member of the Low Power Radio Association.



Information contained in this document is believed to be accurate, however no representation or warranty is given and no liability is assumed by R.F. Solutions Ltd. with respect to the accuracy of such information. Use of R.F.Solutions as critical components in life support systems is not authorised except with express written approval from R.F.Solutions Ltd.