



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Screwdriver - SZS 0,6X2,5 - 1205040

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Screwdriver, bladed, VDE insulated, size: 0.6 x 2.5 x 80 mm, 2-component grip, with non-slip grip

The illustration shows version
SZS 0,6 x 3,5

Why buy this product

- The tools feature ergonomic two-component safety handles
- Large contact surface of blades inside screw head
- Individually tested safety screwdrivers according to DIN EN 60900 (VDE 0682-201)
- For working on or in the vicinity of live parts up to 1000 V AC or 1500 V DC

Key commercial data

Packing unit	1
Minimum order quantity	10
Catalog page	Page 283 (CL2-2011)
GTIN	 4 017918 019082
Custom tariff number	82054000
Country of origin	CZECH REPUBLIC

Technical data

General

Length (b)	161 mm
Width (a)	26 mm
Design	Phillips
Blade thickness	0.6 mm
Blade width	2.5 mm
Blade height	80 mm
Weight	30 g
Test standard	DIN/ISO 2380-1 IEC 60900:2004

Classifications

eclass

eCl@ss 4.0	21040401
------------	----------

Screwdriver - SZS 0,6X2,5 - 1205040

Classifications

eclass

eCl@ss 4.1	21040401
eCl@ss 5.0	21040401
eCl@ss 5.1	21040401
eCl@ss 6.0	21040401
eCl@ss 7.0	21040409

etim

ETIM 2.0	EC000158
ETIM 3.0	EC000158
ETIM 4.0	EC000158

unspsc

UNSPSC 6.01	27111701
UNSPSC 7.0901	27111701
UNSPSC 11	27111701
UNSPSC 12.01	27111701
UNSPSC 13.2	27111701

Approvals

Approvals

Approvals


VDE approval of drawings / GOST

Ex Approvals

Approvals submitted

Approval details

VDE approval of drawings 
--

GOST 
--

Drawings

Screwdriver - SZS 0,6X2,5 - 1205040

Pictogram



Dimensioned drawing

