



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Crimping Device

CF 3000-2,5

Portable Crimping Device CF 3000-2,5

The automatic stripping and crimping device, CF 3000 processes taped ferrules with insulating sleeves according to DIN 46 228-4 in an extremely efficient way. Using this device, up to 1200 conductors per hour can be stripped and fitted with ferrules in one operation. The light weight of the CF 3000 of only approx. 13 kg fulfills the wish of many users.

The crimping device is suitable for both preassembling and attaching conductors directly at the control cabinet. The device can be adapted to various cross section areas 0.5 mm² up to 2.5 mm² within a minute. For further properties, please refer to the technical data.



Portable Crimping Device CF 3000-2,5, for Taped Products



CF 3000-2,5

1. Technical Data

Portable crimping device CF 3000-2,5

1.1 Description

Automatic stripping and crimping device,
for insulated taped ferrules, 0.5-2.5 mm²
according to DIN 46 228-4: 1990-09

Automatic stripping and crimping device, 120 V design,
for insulated taped ferrules, 0.5-2.5 mm²
according to DIN 46 228-4: 1990-09

Type	Order No.	Pcs. Pkt.
CF 3000-2,5	12 05 47 7	1
CF 3000-2,5 120V	12 05 51 6	1

1.2 Description / Accessories

		Type	Order No.	Pcs. Pkt.
Ferrules, with plastic insulation sleeve, 0.5 mm ²	white	AI 0,5-8 WH-B ¹⁾	32 01 36 9	1000
	orange	AI 0,5-8 OG-B	32 01 56 3	1000
Ferrules, as above, however 0.75 mm ²	gray	AI 0,75-8 GY-B ¹⁾	32 01 37 2	1000
	blue	AI 0,75-8 BU-B	32 01 54 7	1000
	white	AI 0,75-8 WH-B	32 01 57 6	1000
Ferrules, as above, however 1.0 mm ²	red	AI 1,0-8 RD-B ¹⁾	32 01 38 5	1000
	yellow	AI 1,0-8 YE-B	32 01 58 9	1000
Ferrules, as above, however 1.5 mm ²	black	AI 1,5-8 BK-B ¹⁾	32 01 39 8	1000
	red	AI 1,5-8 RD-B	32 01 59 2	1000
Ferrules, as above, however 2.5 mm ²	blue	AI 2,5-8 BU-B ¹⁾	32 01 40 8	500
	gray	AI 2,5-8 GY-B	32 01 55 0	500

¹⁾ Color range acc. to DIN 46 228-4: 1990-09.

1.3 Technical data

Dimensions		
Width / length / height	[mm]	165 / 320 / 300
Weight	[kg]	13
Cycle	[s]	1.2
Area of application		
Conductor	[mm ²]	0.5 - 2.5
Conductor	[AWG]	20 - 14
Mains connection	[V AC / Hz]	230 / 50
Power consumption	[VA]	80
Compression		trapezoidal acc. to DIN VDE 0660-100: 1992-07

<http://www.phoenixcontact.com>

TNR: 5127849-00

© PHOENIX CONTACT 31.01.03