



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832




Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



MATERIAL NO.	ENGINEERING NO.	LENGTH	POLES
1206142003	LW04006K03M020	78.7 (2M)	4
1206142004	LW05006K03M020	78.7 (2M)	5

NOTICE: THIS PART IS CSA AND FACTORY MUTUAL APPROVED
NO CHANGES CAN BE MADE TO THE ASSEMBLY, COMPONENTS
OR SUPPLIER WITHOUT PRIOR APPROVAL FROM CSA AND
FACTORY MUTUAL.



- NOTES:
1. MATERIAL: SEE TABLE
 2. FINISHES: SEE TABLE
 3. PRODUCT SPECIFICATIONS: PS-120614-001
 4. CONTROL DOC: ES-120614-001
 5. 3 & 4 POLE ELECTRICAL SPECIFICATIONS:
VOLTAGE RATING: 125V
CURRENT RATING: 4 AMPS
 6. 5 POLE ELECTRICAL SPECIFICATIONS:
VOLTAGE RATING: 32V
CURRENT RATING: 4 AMPS

② LW0X006K03MXXX

SINGLE END
POLE QTY.
HEAD STYLE
CABLE TYPE
FINISHED LENGTH
REF. XXX = METERS
EXAMPLE 010 = 1M

MALE FACE VIEW

3 POLE	4 POLE	5 POLE
1 BROWN 3 BLUE 4 BLACK	1 BROWN 2 WHITE 3 BLUE 4 BLACK	1 BROWN 2 WHITE 3 BLUE 4 BLACK 5 GRAY

8	1	WRAP LABEL	PLASTIC FILM	BLACK/YELLOW
7	1	FLAG LABEL (WARNING)	POLYESTER	BLACK/ORANGE
6	1	OVERMOLD	TPE	YELLOW
5	1	OUTER SLEEVE	ST. STEEL	PASSIVATED
4	1	INNER SLEEVE	ST. STEEL	PASSIVATED
3	XX	CONTACT	Cu ALLOY	GOLD PLATED
2	1	INSERT	PUR	BLACK
1	1	CABLE, #18 AWG ITC/PLTC	TPE	YELLOW
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH

ADDED P/N LEGEND	DESCRIPTION
EC NO: JG2014-0138	2013/07/23
DRWN:RSTONE	2013/08/01
CHKD:B WOODMAN	2013/12/30
APPR:WOODMAN	
REV	DESCRIPTION
B	

QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)
▽=0	
▽=0	
	mm INCH
	4 PLACES ± --- ± ---
	3 PLACES ± --- ± ---
	2 PLACES ± --- ± .01
	1 PLACE ± 0.3 ± ---
	ANGULAR ± 2 °
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS


DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
IN/MM	1.5:1	INCH	
DRAWN BY	DATE	TITLE	
RSTONE	2011/11/21	ULTRA-LOCK ZONE 2	
CHECKED BY	DATE	MALE, STRAIGHT	
L. HARTMANN	2012/01/27	K03.18AWG, TPE	
APPROVED BY	DATE		
JFMURPHY	2012/04/18		
MATERIAL NO.	DOCUMENT NO.		
SEE CHART	SD-120614-013		
SIZE			
C			

DRAWING NO.	DESCRIPTION	FINISHED GOOD REV. LEVEL
LWR000A18	MIC U-LOCK ZONE 2 RECEPT ASSY, FEM. 1/2 NPT, 22 AWG	C
LWR006A18	MIC U-LOCK ZONE 2 RECEPT ASSY, MALE 1/2 NPT, 22 AWG	B
LWRA00A18	MIC U-LOCK ZONE 2 RECEPT ASSY, FEM. 1/4 NPT, 22 AWG	C
LWRA06A18	MIC U-LOCK ZONE 2 RECEPT ASSY, MALE 1/4 NPT, 22 AWG	B
LWR000A16	MIC U-LOCK ZONE 2 RECEPT ASSY, FEM. 1/2 NPT, 18 AWG	B
LWR006A16	MIC U-LOCK ZONE 2 RECEPT ASSY, MALE 1/2 NPT, 18 AWG	B
LWXXXXXXC02XXXX	U-LOCK ZONE 2 C02 CORD ASSY, 18AWG SJ00W, DC COLOR	C
LWXXXXXXK03XXXX	U-LOCK ZONE 2 K03 CORD ASSY, 18AWG TPE, DC COLOR	C
LWXXXXXXK05XXXX	U-LOCK ZONE 2 K05 CORD ASSY, 22AWG TPE, DC COLOR	C
SD-120614-999	CONTROL DOC FOR ULTRA-LOCK ZONE 2	D

PRELIMINARY EC NO: IPG2016-0500 DRAWN: RSTONE 2016/03/07 CHKD: WAI LEUNG 2016/05/20 APPR: JFMURPHY 2016/05/20 A	DESCRIPTION	QUALITY SYMBOLS ▽=0 ◻=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE 1:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	
					DRAWN BY RSTONE		DATE 2016/03/07		TITLE SCHEDULE DRAWING FOR ULTRA LOCK ZONE 2	
					CHECKED BY WAI LEUNG		DATE			
					APPROVED BY JFMURPHY		DATE 2016/05/20		molex	
					MATERIAL NO. -		DOCUMENT NO. SD-120614-998			
			ANGULAR ± ---°		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			


CLASS 1, DIVISION 2, GROUP A, B, C, OR D
HAZARDOUS LOCATION

NON-HAZARDOUS LOCATION



CLASS 1, DIVISION 2, GROUP A, B, C, OR D
HAZARDOUS LOCATION

NON-HAZARDOUS LOCATION



NOTICE: THIS PART IS CSA AND FACTORY MUTUAL APPROVED
NO CHANGES CAN BE MADE TO THE ASSEMBLY, COMPONENTS
OR SUPPLIER WITHOUT PRIOR APPROVAL FROM CSA AND
FACTORY MUTUAL.

NOTES:

1. THE INSTALLATION MUST BE IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC), ANSI/NFPA 70. SPECIFIC REQUIREMENTS FOR THE INSTALLATION OF ITC RATED CABLE MAY BE FOUND IN ARTICLE 501.4(B)(1)(5) AND ARTICLE 727.4
2. THE MOLDED CONSTRUCTION OF THE CORDSET AND GAS/VAPORTIGHT CONTINUOUS SHEATH OF THE CABLE MEET THE REQUIREMENTS OF THE NEC, ARTICLE 501-5(E)(2) FOR CABLE SEALS IN CLASS 1, DIVISION 2
4. ATEX cert no: ATEX FM15ATEX0048X IECEx FMG 15.0012X ①


FIELD DEVICE APPROVAL FOR CLASS 1, DIV. 2
OR CLASS 1, ZONE2 INSTALLATIONS

REF. SEE SHEET 3 FOR CONFIGURATION INFORMATION

THIS DRAWING SUPERSEDES ES-120614-001 REV-B

ADDED NOTE 4 EC NO: IPG2016-0500 2015/10/16 DRAWNR: STONE 2016/05/20 CHKD: WAI LEUNG APPR: JFMURPHY 2016/05/20	QUALITY SYMBOLS ▽=0 ▽=0	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE 1:1	DESIGN UNITS INCH	 THIRD ANGLE PROJECTION		
				mm	INCH	DRAWN BY RSTONE	DATE 2012/05/18	TITLE CONTROL DOC FOR ULTRA-LOCK ZONE 2			
			4 PLACES	± ---	± ---	CHECKED BY K JOZWIK	DATE 2012/05/22				
			3 PLACES	± ---	± ---	APPROVED BY JFMURPHY	DATE 2012/08/27	 MOLEX INCORPORATED			
			2 PLACES	± ---	± ---	MATERIAL NO. 1206149999	DOCUMENT NO. SD-120614-999	SHEET NO. 1 OF 3			
		REV	ANGULAR ± ---°		SIZE C		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS								

HAZARDOUS LOCATION



LWR X A06 A18 CXXX
(MALE 1/4" NPT)

LWR X A00 A18 CXXX
(FEMALE 1/4" NPT)

A technical drawing of a long, thin mechanical component, possibly a shaft or rod. It features a handle or fitting on the left end and a circular component with a central hole on the right end. The shaft has several small, evenly spaced holes along its length.

This technical drawing shows a long, slender mechanical component, possibly a shaft or a rod. It features a central section with a series of parallel lines, indicating a threaded or grooved surface. The ends of the component are detailed with flanges or mounting brackets, which are labeled with 'G' and 'H' respectively. The drawing is a precise line drawing, typical of engineering specifications.

1. SEE SHEET 1 FOR NOTES
2. SEE SHEET 3 FOR CONFIGURATION INFORMATION

SEE SHEET 1
EC NO: PG2016-0500
DRAWN: RSTONE 2015/10/16
CHECKED: WAI LEUNG 2016/05/20
APPR: JFMURPHY 2016/05/20

GENERAL TOLERANCES
(UNLESS SPECIFIED)

DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONS

DRAWN BY	DATE
RSTONE	2012/05/18
CHECKED BY	DATE
K JOZWIK	2012/05/22
APPROVED BY	DATE
JFMURPHY	2012/08/27

©  THIRD ANGLE
PROJECTION

MOLEX INCORPORATED

DOCUMENT NO. SD-120614-999	SHEET NO. 2 OF 3
-------------------------------	---------------------

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

M12/MICROCHANGE ULTRA-LOCK CORD CONNECTORS AND CORD SETS

LWO 3 000 C02 M 020 8
I II III IV V VI VII

I: CONNECTOR TYPE
LWO= ULTRA-LOCK ZONE 2 MALE OR FEMALE SINGLE END CORDSET
LWV= ULTRA-LOCK ZONE 2 FEMALE TO STANDARD ULTRA-LOCK MALE DOUBLE ENDED CORDSET
WLW= ULTRA-LOCK ZONE 2 MALE TO STANDARD ULTRA-LOCK FEMALE DOUBLE ENDED CORDSET
LW8= ULTRA-LOCK ZONE 2 FEMALE TO STANDARD M12 MALE DOUBLE ENDED CORDSET
8LW= ULTRA-LOCK ZONE 2 MALE TO STANDARD M12 FEMALE DOUBLE ENDED CORDSET
LWLW= ULTRA-LOCK ZONE 2 FEMALE TO ULTRA-LOCK ZONE 2 MALE DOUBLE ENDED CORDSET

II: NUMBER OF POLES: 3= 3 PIN, 4= 4 PIN, 5 = 5 PIN

III: CONFIGURATION
SINGLE ENDED:
000= STRAIGHT FEMALE CONNECTOR
001= FEMALE 90°
006= STRAIGHT MALE, EXTERNAL THREAD
007= MALE 90°

DOUBLE ENDED:
030= STRAIGHT FEMALE CONNECTOR TO STRAIGHT MALE CONNECTOR
031= FEMALE 90° TO MALE STRAIGHT
032= FEMALE STRAIGHT TO MALE 90°
033= FEMALE 90° TO MALE 90°

IV: CABLE TYPE
C02= SJ00W YELLOW, 18 AWG, DC CODE
K03= PLTC/ITC, 18 AWG, TPE JACKET
K05= PLTC/ITC, 22 AWG, TPE JACKET

V: UNIT OF MEASURE
F= FEET
M= METERS

VI: CABLE LENGTH (MAY BE ANY 3 DIGIT NUMBER FROM 001-100)
1ST DIGIT= 10 X LENGTH
2ND DIGIT= 1 X LENGTH
3RD DIGIT= .1 X LENGTH

VII: COUPLING NUT MATERIAL
ULTRA-LOCK ZONE 2 END(S) ARE STAINLESS STEEL

M12 OR ULTRA-LOCK:
NONE = STANDARD MATERIAL (NICKEL PLATED BRASS)
8= STAINLESS STEEL

NOTICE: THIS PART IS CSA AND FACTORY MUTUAL APPROVED
NO CHANGES CAN BE MADE TO THE ASSEMBLY, COMPONENTS
OR SUPPLIER WITHOUT PRIOR APPROVAL FROM CSA AND
FACTORY MUTUAL.

M12/MICROCHANGE ULTRA-LOCK OUTLETS

LWR 3 A00 A18 M 020 8
I II III IV V VI VII

I: CONNECTOR TYPE
LWR= LOCKING INLETS AND OUTLETS

II: NUMBER OF POLES 3=3 PIN, 4= 4 PIN, & 5= 5 PIN

III: CONFIGURATION
SINGLE ENDED:
A00= FEMALE STRAIGHT (INT.THEAD) 1/4-18 NPT
A06= MALE STRAIGHT (EXT.THEAD) 1/4-18 NPT
000= FEMALE STRAIGHT (INT.THEAD) 1/2-14 NPT
006= MALE STRAIGHT (EXT.THEAD) 1/2-14 NPT

IV: WIRE TYPE
A18= 22 AWG, PVC, DC COLOR CODE, UL TYPE 1061
A16= 18 AWG, PVC, DC COLOR CODE, UL TYPE 1569
000= PCB PINS
000= PCB PINS

V: UNIT OF MEASURE
A= INCHES
F= FEET
C= CENTIMETERS
M= METERS

VI: WIRE LENGTH (MAY BE ANY 3 DIGIT NUMBER FROM 001-100)
1ST DIGIT= 10 X LENGTH
2ND DIGIT= 1 X LENGTH
3RD DIGIT= .1 X LENGTH

VII: SHELL MATERIAL
M12 OR ULTRA-LOCK:
NONE = STANDARD MATERIAL (COPPER ZINC ALLOY)
3= NICKEL PLATED BRASS
8= STAINLESS STEEL

SEE SHEET 1 EC NO: IPG2016-0500 DRAWN BY: DRWINRSTONE 2015/10/16 CHKD BY: CHKD-WAI LEUNG 2016/05/20 APPR: JFMURPHY 2016/05/20 D	DESCRIPTION REV	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE 1:1	DESIGN UNITS INCH	 THIRD ANGLE PROJECTION		
				mm	INCH	DRAWN BY	DATE	TITLE CONTROL DOC FOR ULTRA-LOCK ZONE 2			
			4 PLACES	± ---	± ---	RSTONE	2012/05/18				
			3 PLACES	± ---	± ---	CHECKED BY	DATE				
			2 PLACES	± ---	± ---	K JOZWIK	2012/05/22				
			1 PLACE	± ---	± ---	APPROVED BY	DATE	 MOLEX INCORPORATED			
			ANGULAR ± ---°		JFMURPHY	2012/08/27					
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. 1206149999		DOCUMENT NO. SD-120614-999		SHEET NO. 3 OF 3					
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION											