

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Tool - CF 1000-1,5 120V - 1208209

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



Automatic stripping and crimping device, 120 V version, for insulated taped ferrules with a cross section range of 0.5- 2.5 mm^2 in acc. with DIN 46228-4: 1990-09

Why buy this product

- Rugged design
- Quick change of cross section without the need for additional adjustments
- Up to 1200 conductors can be processed an hour
- Suitable for bulk processing
- ☑ The pull-out forces meet the requirements of IEC/EN 60999 and IEC/EN 60947
- The stripping and crimping machine can be used to process loose ferrules with insulating collars according to DIN 46228-4
- ☑ Quantity counter
- The conductor is stripped in a single step and crimped with a ferrule to a high standard of quality

Key commercial data

Packing unit	1
Minimum order quantity	1
Catalog page	Page 332 (CL2-2011)
GTIN	4 046356 011358
Custom tariff number	84798100
Country of origin	GERMANY

Technical data

General

Length (b)	490 mm
Height	390 mm
Width (a)	240 mm
Air consumption per compression	1.21
Working cycle	1.5 s
Weight	29 kg
Test standard	DIN 46228-4: 1990-09
Compression	trapezoidal



Tool - CF 1000-1,5 120V - 1208209

Classifications

eclass

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301
eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	17130101

etim

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001186

unspsc

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518

Accessories

Accessories

Tools

Conversion kit - CF 1000-TOOLKIT 0,34/ 6 - 1208212



Assembly set for CF 1000, for insulated taped ferrules according to DIN 46228-4: 1990-09, cross section range: 0.25-0.34 mm², AWG: 24-22, stripping length: 6 mm

Conversion kit - CF 1000-TOOLKIT 2,5/8 - 1208241



Assembly set for CF 1000, for insulated taped ferrules according to DIN 46228-4: 1990-09, cross section range: 0.5-2.5 mm², AWG: 20-14, stripping length: 8 mm

Conversion kit - CF 1000-TOOLKIT 4,0/10 - 1208270



Assembly set for CF 1000, for insulated taped ferrules according to DIN 46228-4: 1990-09, cross section range: 4 mm², AWG: 12, stripping length: 10 mm



Tool - CF 1000-1,5 120V - 1208209

Accessories

Conversion kit - CF 1000-TOOLKIT 0,34/8 - 1208225



Assembly set for CF 1000, for insulated taped ferrules according to DIN 46228-4: 1990-09, cross section range: 0.25-0.34 mm², AWG: 24-22, stripping length: 8 mm

Spare knife - CF 1000 EM - 1205215

Accessories for CF 1000 stripping and crimping machine, replacement blade for 0.25 - 2.5 mm², V-shaped



© Phoenix Contact 2012 - all rights reserved http://www.phoenixcontact.com