



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



CF 1000-1,5...

Wire Stripping and Crimping Device



CLIPLINE

Data Sheet

© PHOENIX CONTACT - 04/2006

Description

The CF 1000 can be used to:

- fully automatically strip wires or to
- fully automatically strip wires and crimp ferrules to the wires.

Flexible wires of classes 2, 5 and 6 in accordance with DIN VDE 0295 and ferrules as material in bulk in accordance with DIN 46228-4 are processed.

The automatic stripping and crimping device is electropneumatically controlled by a microprocessor. The CF 1000 is available in 120 V or 230 V design.

Thanks to short cycle times and the easy replacement of dies with different cross sections, the CF 1000 is also suitable for use in workshops as well as in complex cable assembly systems.



Make sure you always use the latest documentation.
It can be downloaded at www.download.phoenixcontact.com.
A conversion table is available on the Internet at
www.download.phoenixcontact.com/general/7000_en_00.pdf.



This data sheet is valid for all products listed on the following page:

Ordering Data

Automatic Stripping and Crimping Device

Description	Type	Order No.	Pcs./Pkt
Automatic stripping and crimping device 230 V design for insulated ferrules in acc. with DIN 46228-4, for cross sections from 0.5 mm ² ... 1.5 mm ²	CF 1000-1,5 230V	1208199	1
Automatic stripping and crimping device 120 V design for insulated ferrules in acc. with DIN 46228-4, for cross sections from 0.5 mm ² ... 1.5 mm ²	CF 1000-1,5 120V	1208209	1

Tool Kits

Description	Type	Order No.	Pcs./Pkt
Tool kit for insulated ferrules in acc. with DIN 46228-4, for cross sections:			
0.25 mm ² ... 0.34 mm ² , stripping length 6 mm	CF 1000-TOOLKIT 0,34/ 6	1208212	1
0.25 mm ² ... 0.34 mm ² , stripping length 8 mm	CF 1000-TOOLKIT 0,34/ 8	1208225	1
0.5 mm ² ... 2.5 mm ² , stripping length 8 mm	CF 1000-TOOLKIT 2,5/ 8	1208241	1
4 mm ² , stripping length 10 mm	CF 1000-TOOLKIT 4,0/10	1208270	1

Technical Data

General Data

Mains connection	CF 1000-1,5 230V	230 V/50 Hz
	CF 1000-1,5 120V	120 V/60 Hz
Power rating		0.5 A
Compressed air port		4 bar, min. up to 6 bar, max. 1/4"-plug nipple internal thread (European standard)
Compressed air consumption		1.2 l/stroke
Cycle time		1.5 s
Operating range		0.5 mm ... 2.5 mm
Ferrules		Material in bulk in acc. with DIN 46228-4
Pressing unit		Trapezoidal
Conductors		Classes 2, 5 and 6 as per DIN VDE 0295
Controller		Electrical / pneumatic with microprocessor
Counter		Mech. display, 5-digit, resetable
Dimensions (W x H x D)		240 mm x 390 mm x 490 mm
Weight		29 kg