



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Voltage tester - PROFIPOL - 1209101

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Voltage tester, for DC and AC voltages of 6 V to 400 V, IP65

Why buy this product

- Shock-proof, dust-proof, and splash-proof housing, IP65
- DC and AC voltage tests in the range from 6 V to 400 V
- Polarity test (+/-) for DC voltage
- LED indicator

Key commercial data

Packing unit	0
Minimum order quantity	1
Catalog page	Page 294 (CL2-2011)
GTIN	 4 046356 309899
Custom tariff number	90303310
Country of origin	IRELAND

Technical data

General

Color	black
Ambient temperature (operation)	-10 °C ... 55 °C
Degree of protection	IP65
Voltage supply	2 x micro battery 1.5 V, LR03, AAA
Test certificate	EN/IEC 61243-3 (VDE 0682 Part 401)
Display scope	12 V, 24 V, 50 V, 120 V, 230 V, 400 V AC/DC diode display LED
Phase display	LED
Polarity display	LED (symbol "+/-")
Innenwiderstand_Messkreis	130.00 kΩ
Minimum voltage	6 V DC
Max. voltage	400 V DC
Minimum voltage	6 V AC
Max. voltage	400 V AC

Voltage tester - PROFIPOL - 1209101

Classifications

eclass

eCl@ss 4.0	27200312
eCl@ss 4.1	27200301
eCl@ss 5.0	27200301
eCl@ss 5.1	27200301
eCl@ss 6.0	27200301
eCl@ss 7.0	27200301

etim

ETIM 2.0	EC000149
ETIM 3.0	EC000149
ETIM 4.0	EC000494

unspsc

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

Approvals

Approvals

Approvals

VDE approval of drawings

Ex Approvals

Approvals submitted

Approval details

VDE approval of drawings 
--
