



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




Replacement die - CRIMPFOX-M 10/DIE - 1212080

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Die, for Crimpfox-M, for ferrules 0.25 - 10 mm², packed in a serial storage box

Key commercial data

Packing unit	0
Minimum order quantity	1
Catalog page	Page 280 (CL2-2011)
GTIN	 4 046356 454506
Custom tariff number	82032000
Country of origin	SWEDEN

Technical data

General

Length (b)	114 mm
Height	25.5 mm
Width (a)	75 mm
Color	black
Weight	86 g
Die station	Crimping position 1
Min. cross section	0.25 mm ²
Max. cross section	0.75 mm ²
AWG min	24
AWG max	20
Die station	Crimping position 2
Min. cross section	1 mm ²
Max. cross section	1.5 mm ²
AWG min	18
AWG max	16
Die station	Crimping position 3
Max. cross section	2.5 mm ²
AWG max	14
Die station	Crimping position 4
Max. cross section	4 mm ²

Replacement die - CRIMPFOX-M 10/DIE - 1212080

Technical data

General

AWG max	12
Die station	Crimping position 5
Max. cross section	10 mm ²
AWG max	10
Compression	Trapezoidal crimp
Type of contact	Ferrules

Classifications

eclass

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301
eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	21043811
eCl@ss 7.0	21043811

etim

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001186

unspsc

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518

Approvals

Approvals

Approvals

GOST

Ex Approvals

Approvals submitted

Replacement die - CRIMPFOX-M 10/DIE - 1212080

Approvals

Approval details

GOST 

© Phoenix Contact 2012 - all rights reserved
<http://www.phoenixcontact.com>