



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Replacement die - CRIMPFOX-M SC 1/DIE - 1212083

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Die, for Crimpfox-M, for non-insulated slip-on sleeves 0.1 - 1 mm², packed in a serial storage box

### Key commercial data

Packing unit	0
Minimum order quantity	1
Catalog page	Page 280 (CL2-2011)
GTIN	 4 046356 454537
Custom tariff number	82032000
Country of origin	SWEDEN

### Technical data

#### General

Length (b)	114 mm
Height	25.5 mm
Width (a)	75 mm
Color	black
Weight	72 g
Die station	Crimping position 1
Min. cross section	0.1 mm²
Max. cross section	0.25 mm²
AWG min	26
AWG max	24
Die station	Crimping position 2
Min. cross section	0.25 mm²
Max. cross section	0.5 mm²
AWG min	24
AWG max	22
Die station	Crimping position 3
Min. cross section	0.5 mm²
Max. cross section	1 mm²
AWG min	22
AWG max	18

# Replacement die - CRIMPFOX-M SC 1/DIE - 1212083

## Technical data

### General

Compression	B crimp
Type of contact	Slip-on sleeve

## Classifications

### eclass

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301
eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	21043811
eCl@ss 7.0	21043811

### etim

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001186

### unspsc

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518

## Approvals

### Approvals

#### Approvals

#### GOST

#### Ex Approvals

#### Approvals submitted

### Approval details

GOST 
--

