



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Pneumatic crimping tool - ZAP 40 - 1212630

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Pneumatic crimping pliers, for ferrules according to DIN 46228-1: 1992-08 and DIN 46228-4: 1990-09, for conductor cross section 0.25 - 4 mm<sup>2</sup>, trapezoid crimping, lateral entry



### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	720.0 GRM
Custom tariff number	84678900
Country of origin	Germany

### Technical data

#### Dimensions

Length (b)	190 mm
------------	--------

#### General

Compression	trapezoidal
Min. AWG, flexible, multi-strand	12
AWG max., flexible, multi-strand	2
Pressure range	4 bar ... 6 bar
Air consumption per compression	0.2 l

### Classifications

#### eCl@ss

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301

# Pneumatic crimping tool - ZAP 40 - 1212630

## Classifications

### eCl@ss

eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	17130101
eCl@ss 7.0	17130101
eCl@ss 8.0	17130101

### ETIM

ETIM 3.0	EC001186
ETIM 4.0	EC001186
ETIM 5.0	EC002778

### UNSPSC

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518

## Accessories

### Accessories

#### Connector

Ferrule - AI 0,25- 6 YE - 3203024



Ferrule, Sleeve length: 6 mm, Length: 10.5 mm, Color: yellow

Ferrule - AI 0,25- 8 YE - 3203037



Ferrule, Sleeve length: 8 mm, Length: 12.5 mm, Color: yellow

## Pneumatic crimping tool - ZAP 40 - 1212630

### Accessories

Ferrule - AI 0,5 - 8 WH - 3200014



Ferrule, Sleeve length: 8 mm, Length: 14 mm, Color: white

---

Ferrule - AI 0,5 -10 WH - 3201275



Ferrule, Sleeve length: 10 mm, Length: 16 mm, Color: white

---

Ferrule - AI 0,75- 8 GY - 3200519



Ferrule, Sleeve length: 8 mm, Length: 14 mm, Color: gray

---

Ferrule - AI 0,75-10 GY - 3201288



Ferrule, Sleeve length: 10 mm, Length: 16 mm, Color: gray

---

Ferrule - AI 1 - 8 RD - 3200030



Ferrule, Sleeve length: 8 mm, Length: 14 mm, Color: red

---

## Pneumatic crimping tool - ZAP 40 - 1212630

### Accessories

Ferrule - AI 1 -10 RD - 3200182



Ferrule, Sleeve length: 10 mm, Length: 16 mm, Color: red

---

Ferrule - AI 1,5 - 8 BK - 3200043



Ferrule, Sleeve length: 8 mm, Length: 14 mm, Color: black

---

Ferrule - AI 1,5 -10 BK - 3200195



Ferrule, Sleeve length: 10 mm, Length: 18 mm, Color: black

---

Ferrule - AI 2,5 -10 BU - 3202533



Ferrule, Sleeve length: 10 mm, Length: 17 mm, Color: blue

---

Ferrule - AI 2,5 -12 BU - 3200962



Ferrule, Sleeve length: 12 mm, Length: 18 mm, Color: blue

---

## Pneumatic crimping tool - ZAP 40 - 1212630

### Accessories

Ferrule - AI 4 -10 GY - 3200535



Ferrule, Sleeve length: 10 mm, Length: 17 mm, Color: gray

---

Ferrule - AI 4 -12 GY - 3200959



Ferrule, Sleeve length: 12 mm, Length: 19 mm, Color: gray

---

---