



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




EVEREADY 1235

C
SUPER HEAVY DUTY




Industry Standard Dimensions




- Chemical System:** Zinc-Manganese Dioxide (Zn/MnO₂)
(No Added Mercury or Cadmium)
- Designation:** ANSI-14D, IEC-R14
- Battery Voltage:** 1.5 Volts
- Operating Temp:** -18°C to 55°C (0°F to 130°F)
- Average Weight:** 45.0 grams (1.6 oz.)
- Volume:** 25 cubic centimeters (1.5 cubic inch)
- Average Capacity:** 3800 mAh to 0.8 volts
(Rated at 25 mA continuous at 21°C)
- Cell:** One No. 35 (size "C")
- Jacket:** Metal


TYPICAL TEMPERATURE EFFECT
3.9 ohm - 4 hours/ day to 0.75 volts



CONSTANT RESISTANCE PERFORMANCE
Typical Service



CONSTANT CURRENT DISCHARGE
Typical Service



Important Notice

This data sheet contains information specific to batteries manufactured at the time of its publication.


Contents herein do not constitute a warranty.

Copyright © Eveready Battery Co. - All rights reserved


EVEREADY 1235

Industry Standard Tests (21° C)


RADIO
20 ohm - 4 hours/ day




PORTABLE STEREO
6.8 ohm - 1 hr/ day



TOY
3.9 ohm - 1 hr/ day



PORTABLE LIGHT
3.9 ohms - 4 min/ hour 8 hours/ day



Important Notice

This data sheet contains information specific to batteries manufactured at the time of its publication.

Contents herein do not constitute a warranty.

Copyright © Eveready Battery Co. - All rights reserved