

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







DESCRIPTION 18-4 POLYURETHANE CORD

OUTER JACKET:

COLOR: YELLOW (MUNSELL 5Y 8/12) FLAME RETARDENT POLYURETHENE (UL 20549)

DIA: .275" ±.010"

THICKNESS: .020" NOMINAL

IMPRINT: SU AWM STYLE 20549 4C/18 VW1 (NOTE 5) (NOTE 6) CSA AWM

I/Ⅲ A/B 80°C 300V FT1.

IMPRINT STYLE: BLACK HELVETICA LIGHT, 3/32" TALL AND 12" REPEAT.

INNER JACKET:

COLOR: BLACK POLYVINYL CHLORIDE (UL 20549)

DIA.: .226 ±.010"

THICKNESS: .020" NOMINAL

CONDUCTOR:

STRANDING: 41 X #34 STRANDED TINNED COPPER.

INSULATION DIA: .070 NOMINAL

INSULATION THICKNESS: .009 NOMINAL

INSULATION MATERIAL: POLYVINYL CHLORIDE (UL 1731)

CONSTRUCTION:

CABLING: 1-1/2" LEFT HAND LAY

FILLER: NON-WICKING MATERIAL ONLY TO ENSURE ROUNDNESS


RATING:

UL: STYLE 20549 80°C 300V

CSA: CERTIFIED AWM CLASS I/II GROUP A/B FT1

MECHANICAL CHARACTERISTICS:

COLOR ROTATION	CRITICAL
DIRECTION OF PRINT	CRITICAL



(FACE VIEW MALE)