

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







# STATSHIELD® ESD SHIELDING BAG METAL OUT CONSTRUCTION STATIC SENSITIVE HARBOLE ONLY VAT HARBOLE ONLY VAT Madio Le America variancescholeuries com Weld Seal Width (W) Side Weld Seals 3/8 in. (±0.10)





### Mixed Unsortable Plastic Scrap

Mixed unsortable plastic scrap shall contain assorted plastics of multiple grades that are co-extruded, bonded or laminated together which are unsortable into individual grades

Desco's bags are recyclable

Statshield® bags are packaged 100 per package in an oversized shielding bag. Shelf life of bags is minimum one year in normal indoor storage conditions.

# DESCO

### STATSHIELD® METAL-OUT SERIES

### **Specifications:**

**Electrical Properties** Test Procedures/Method **Typical Values** Surface Resistance: Outer Surface <10E8 ohms ANSI/ESD STM11.11 Inner Surface <10E11 ohms ANSI/ESD STM11.11 Static Shielding <25 nJ ANSI/ESD STM11.31, EIA 541 Charge Generation (nC/in<sup>2</sup>) Teflon: -0.03 Modified Incline Plane Quartz: +0.10 Modified Incline Plane

**Physical Properties:** 

Capacitance Probe (to dissipate 1 KV)

Bag Thickness: Thickness Nominal .0030" (.0762mm) ±10% MIL-STD-3010, 1003 Width (Inside Dimensions) Nominal -0" / + .125" Length (Inside Dimensions) Nominal ± .125" Light Transmission 40% (Tobias) ASTM D-1003 Tensile 9000 PSI ASTM D882 Puncture Resistance >10 lbs MIL-STD-3010, 2065 **MVTR** 0.40 ASTM F-1249 Heat Seal >10 lbs/in. 375°F, 1/2 sec 60 psi Outgassing Pass ASTM E595 Non-corrosive Pass MIL-STD-3010, M3005

<30 volts

**Chemical Properties** 

Corrosion: No effect on aluminum, copper, silver, Sn-Pb coated foil,

stainless steel, low carbon steel

Polycarbonate compatible: Contains no Amines, Amides, or N-Octanoic Acid.

Bag is free of amines, N-octanoic acid, silicones, and heavy metals.

### ANSI/ESD S541 Section 6.2 Outside an EPA

"Transportation of sensitive products outside of an EPA shall require packaging that provides:

- 1. Low charge generation
- 2. Dissipative or conductive materials for intimate contact
- 3. A structure that provides electrostatic discharge shielding."

### **RoHS and REACH Compliance Statement**

None of the RoHS restricted materials or REACH substances of very high concern are intentionally added in manufacturing this product. Ref: Directive 2002/95/EC Article 4.1. and Regulation (EC) No. 1907/2006. See Desco Industries Inc. Limited Warranty at Desco.com.

The bag's material meets the required limits of ANSI/ESD S541 per ANSI/ESD S20.20.

Statshield® and Statfree® are Registered Trademarks of Desco Industries Inc.

Specifications and procedures subject to change without notice.



STATSHIELD® BAG, SHIELDING, METAL-OUT CONSTRUCTION, .0030" (.0762mm)

**DESCO WEST:** 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: <u>Desco.com</u> PHONE (909) 627-8178 FAX (909) 627-7449

**DESCO EAST:** ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370 FAX (781) 575-0172

DRAWING NUMBER 13010

ANSI/EIA-541/Appendix E, 1kV Discharge

DATE: October 2011