

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









PART NUMBER	PAIRS	COND	A SPAN	B SPAN	
			Inches (mm)	Inches	(mm)
132-2801-010	5	10	0.526 (13,36)	0.450 ±.015	(11,43 ±0,38)
132-2801-014	7	14	0.726 (18,44)	0.650 ±.015	(16,51 ±0,38)
132-2801-016	8	16	0.826 (20,98)	0.750 ±.015	(19,05 ±0,38)
132-2801-020	10	20	1.026 (26,06)	0.950 ±.015	(24,13 ±0,38)
132-2801-026	13	26	1.326 (33,68)	1.250 ±.015	(31,75 ±0,38)
132-2801-034	17	34	1.726 (43,84)	1.650 ±.015	(41,91 ±0,38)
132-2801-040	20	40	2.026 (51,46)	1.950 ±.020	(49,53 ±0,51)
132-2801-050	25	50	2.526 (64,16)	2.450 ±.020	(62,23 ±0,51)
132-2801-060	30	60	3.026 (76,86)	2.950 ±.025	(74,93 ±0,64)
132-2801-064	32	64	3.226 (81,94)	3.150 ±.025	(80,01 ±0,64)
132-2801-068	34	68	3.426 (87,02)	3.350 ±.025	(85,09 ±0,64)

PHYSICAL

Conductors: 28 AWG 7/36 Tinned Copper

Insulation: .010" PVC

Laminate: (2) .005" Clear PVC

Color Code: Tan Common: Brown, Red, Orange,

Yellow, Green, Blue, Violet, Gray,

White, Black and Repeat.

Temperature: -40°C to 80°C

ELECTRICAL

Impedance: 100 ohms

Capacitance: 15 pF/ft at 1MHz

Prop Delay: 1.6 ns/ft

DC Res: 65 ohms/1000 ft

Current Rating: 1.3 A at 10°C Rise Above Ambient

Voltage Rating: 300 V

Insulation Res: 10^{10} ohms – 10 ft minimum

Above Values calculated in the ground-signal Configuration

APPROVALS:

UL AWM Style 2697

CSA AWM

A۱	APHENOL SPECTRA:STR	IP R	ev G
F	UPDATE FORMAT AND LIST MORE CNDTR COUNTS	427	2/22/01
G	UPDATE TEMPERATURE WITH -40°C	8150	3/26/15
REVISION	CHANGES	EC0	DATE

720 SHERMAN AVENUE HAMDEN CT 06514

TEL (203) 281-3200 FAX (203) 281-5872

SHEET 1 OF 1



DOCUMENT NO.

.050" Twist'N'Flat® Planar Cable

132-2801-0XX