



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



The left drawing shows a circular cable cross-section with a diameter of 6.00 [2.36] inches. It features two recommended mounting holes, each with a diameter of 6.50 [2.56] inches, positioned 2.50 [0.98] inches apart from the centerline.

The right drawing shows a cross-section of a cable with a diameter of 5.20 [2.05] inches. It includes a recommended cable stripping dimension of 2.30 [0.90] inches for the outer jacket and a recommended cable stripping dimension of 2.50 [0.98] inches for the inner insulation.



				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007” .315 – 1.180 = ± 0.015” 1.180 – 4.724 = ± 0.020” DO NOT SCALE DRAWING	APPROVALS		DATE		Amphenol Connex							
8					DRAWN	GRS	09/17/08						PART DESCRIPTION SMA BULKHEAD CRIMP JACK (FOR 316/U DOUBLE BRAID CABLE)			
7	HEAT SHRINK TUBING															
6	FERRULE	COPPER	GOLD		1	CHECKED			PART NO. 132176							
5	HEX NUT	BRASS	GOLD		1	ISSUED							DWG. NO. 132176.DWG REV. NC SIZE A SCALE NA			
4	LOCK WASHER	BRASS	GOLD		1	SHEET	1 OF 1									
3	CONTACT PIN	BER. COPPER	GOLD		1											
2	INSULATOR	PTFE	NATURAL		1											
1	BODY	BRASS	GOLD	1												
DESCRIPTION				MATERIAL	FINISH	QTY	CAD FILE C:/132/132176.DWG									